March 29, 2021

## **VIA EMAIL**

Board of Selectmen Town of Oak Bluffs c/o Alice Butler Executive Secretary 56 School Street Oak Bluffs, MA 02557

RE: Application of New Cingular Wireless PCS, LLC d/b/a AT&T ("AT&T") for Grants of Location for Small Cell Wireless Facilities, Including Telecommunication Wires and Wireless Attachments and Appurtenances on Existing or Replacement Utility Poles in the Public Right-of-Way at the Following Locations:

Pole #19/1S - Near 64 Circuit Avenue, Oak Bluffs - CRAN\_RCTB\_OAKB\_002 - Replacement Pole

Pole #48/7 - Across from 35 and 37 Pequot Avenue near Hartford Park - CRAN\_RCTB\_OAKB\_003 - Replacement Pole

Pole #63/2 – Near 2 Pennecook Avenue on the corner of Tuckernuck Avenue and Seaview Avenue, across from Waban Park – CRAN\_RCTB\_OAKB\_004 – Existing Pole

Dear Honorable Members of the Oak Bluffs Board of Selectmen:

We represent New Cingular Wireless PCS, LLC (d/b/a "AT&T") with respect to its deployment of small cell facilities in the Town of Oak Bluffs and the Commonwealth of Massachusetts. AT&T is licensed by the Federal Communications Commission (the "FCC") to provide wireless communications services in the Town of Oak Bluffs and throughout the Commonwealth of Massachusetts.

On behalf of AT&T and while reserving all rights, please accept this submission as an application for approval (the "Application") for three (3) small cell wireless facilities installed on existing or replacement utility poles owned by Eversource and located near the above-referenced addresses in Oak Bluffs, MA (the "Sites") pursuant to the federal Telecommunications Act of 1996 (the "Act"), the Declaratory Ruling and Third Report and Order 18-133 (the "Order") issued by the FCC in September 2018 <a href="https://docs.fcc.gov/public/attachments/FCC-18-133A1\_Rcd.pdf">https://docs.fcc.gov/public/attachments/FCC-18-133A1\_Rcd.pdf</a> and Massachusetts General Laws Chapter 166, Section 21,22, 25A for telecommunication wires and wireless attachments and appurtenances installed within the public right-of-way. AT&T has entered into a Pole Attachment Agreement with Eversource and we have included a copy of the licenses issued by Eversource which allows the installations.

Board of Selectmen Town of Oak Bluffs March 29, 2021 Page 2

AT&T's small cell wireless facilities comply and are in accordance with the Act, the Order and Massachusetts law.

We have also provided detailed sets of drawings (the "Plans") and maps for each small cell facility. AT&T has not installed any small cell wireless facilities on Martha's Vineyard yet, so we have provided photographs of similar small cell wireless facilities installed by AT&T on Nantucket as examples. Also enclosed, please find a generic small cell wireless facility radio frequency emissions report demonstrating compliance with applicable exposure to emissions standards established by the FCC.

AT&T proposes these low-power small cell facilities in the Town of Oak Bluffs to deal with the rapidly increasing demands on AT&T's wireless network. These small cell wireless facilities will work in conjunction with the existing macro cell sites installed on rooftops, towers, and other structures in and around the Town of Oak Bluffs. AT&T's radio frequency engineers targeted the proposed locations due to the high traffic and data demands on AT&T's network in the areas near the Sites. Please see the enclosed coverage maps submitted as part of the Application. AT&T's existing macro cell sites are not providing adequate data capacity in the areas near the Sites due to population, network usage, vehicular and foot traffic, multiple wireless devices used by customers and other contributing factors. These small cell facilities will also work to offload the demands on AT&T's macro cell sites and allow for increased data capacity and speed within the immediate vicinity of the Sites and in the areas surrounding the macro cell sites.

As further illustrated on the Plans, the proposed small cell facilities consist of the following:

Pole #19/1S - Near 64 Circuit Avenue, Oak Bluffs — CRAN\_RCTB\_OAKB\_002 — AT&T proposes to install: fiber optic cable(s); remote radios in an equipment cabinet 39" long by 23" wide by 15" deep (7.78 cubic feet in volume) mounted to a 29' 6" replacement wood utility pole at 11' 6" above ground level ("AGL"); a top-mounted antenna measuring 25" long and 10" in diameter (1.22 cubic feet in volume) and antennas measuring 11" long by 8" wide by 5" deep (.25 cubic feet) concealed within an unobtrusive shroud; conduits and cable protectors; and, an electrical meter 8' AGL with shutoff switch and grounding rod.

Pole #48/7 - Across from 35 and 37 Pequot Avenue near Hartford Park – CRAN\_RCTB\_OAKB\_003 - AT&T proposes to install: fiber optic cable(s); remote radios in an equipment cabinet 39" long by 23" wide by 15" deep (7.78 cubic feet in volume) mounted to a 34' replacement wood utility pole at 11' 6" AGL; a top-mounted antennas measuring 25" long and 10" in diameter (1.22 cubic feet in volume) and antenna measuring 11" long by 8" wide by 5" deep

Board of Selectmen Town of Oak Bluffs March 29, 2021 Page 3

(.25 cubic feet) concealed within an unobtrusive shroud; conduits and cable protectors; and, an electrical meter 8' AGL with shutoff switch and grounding rod.

Pole #63/2 – Near 2 Pennecook Avenue on the corner of Tuckernuck Avenue and Seaview Avenue, near the beach across from Waban Park – CRAN\_RCTB\_OAKB\_004 - AT&T proposes to install: fiber optic cable(s); remote radios in a small equipment cabinet 39" long by 23" wide by 15" deep (7.78 cubic feet in volume) mounted to an existing 28' 4" wood utility pole at 11' 6" AGL; a top-mounted antenna measuring 25" long and 10" in diameter (1.22 cubic feet in volume) and antennas measuring 11" long by 8" wide by 5" deep (.25 cubic feet) concealed within an unobtrusive shroud; conduits and cable protectors; and, an electrical meter 8' AGL with shutoff switch and grounding rod.

These small cell facilities will be installed using standard commercially accepted methods in accordance with all applicable federal, state, and local laws, regulations, and orders. All existing wires, streetlights, guy wires, and other attachments will be transferred to the replacement Pole at their current heights. The Plans also provide the proposed locations, pole heights, mounting heights and equipment specifications.

## THE TELECOMMUNICATIONS ACT OF 1996

Without the installation of these small cell facilities, AT&T would be unable to provide specifically established coverage and capacity objectives. The existing utility poles are located within the limited geographic area whereby AT&T's radio frequency engineers determined that a wireless facility is required. The Act imposes substantial restrictions affecting the standard for granting the requested relief. The Act provides that: no laws or actions by any local government or planning or zoning board may prohibit, or have the effect of prohibiting, the placement, construction, or modification of communications towers, antennas, or other wireless facilities in any particular geographic area, see 47 U.S.C. §332(c)(7)(B)(i); local government or planning or zoning boards may not unreasonably discriminate among providers of functionally equivalent services, see 47 U.S.C. §332(c)(7)(B)(i); health concerns may not be considered so long as the emissions comply with the applicable standards of the FCC, see 47 U.S.C. §332(c)(7)(B)(iv); and, decisions must be rendered within a reasonable period of time, see 47 U.S.C. §332(c)(7)(B)(ii) and the Order commonly referenced as the applicable "shot clocks". The FCC shot clocks in these instances are ninety (90) days for the replacement poles and sixty (60) days for the existing pole from the submission of the Application. We also note that the Order redefined "effective prohibition" to mean that state and local governments cannot impose requirements that materially limits or inhibits a provider's ability to engage in activities related to the provision of service. This standard applies to efforts to introduce new or enhance coverage. capacity or service capabilities and notes that regulations that cause a financial burden or competitive disparity can be an effective prohibition.

Board of Selectmen Town of Oak Bluffs March 29, 2021 Page 4

#### **CONCLUSION**

We respectfully assert that AT&T's proposed small cell wireless facilities are reasonable and reasonably comply with the requirements of the Town of Oak Bluffs in light of the Act, the Order and Massachusetts law. AT&T is ready and willing to work cooperatively with the Town of Oak Bluffs with respect the deployment of its small cell wireless facilities. For the foregoing reasons, as well as to satisfy the mandate of the federal government to facilitate competition in the telecommunications industry as set forth in the Act and the Order, AT&T respectfully requests that the Board grant its approval to the Application.

If you have any questions, please don't hesitate to contact us. We look forward to presenting the Application at an upcoming meeting. For the Board's convenience, we have provided a proposed order.

Sincerely,

**BROWN RUDNICK LLP** 

/s/ Edward D. Pare, Jr. Edward D. Pare, Jr., Esq.

Enclosures: Plans

Structural Report License from Utility

Radio Frequency Coverage Maps

Photograph of Existing Small Cell Wireless Facility (Nantucket)

**Emissions Report** 

cc: Robert Whritenour, Town Administrator

#### Alice Butler

From: Sent:

David Ford <dford@clinellc.com> Thursday, April 15, 2021 2:03 PM

To:

Cc:

Alice Butler Vincent Paquette; David Ford

Subject:

RE: AT&T Small Cell // Oak Bluffs, MA - (3) Proposed Wireless Facilities // Grant of Location -

Application Package

Checking in, have we been assigned to a hearing date?

**Thanks** 

David Ford **Centerline Communications** 508.821.6509

From: David Ford <dford@clinellc.com> Sent: Monday, April 5, 2021 10:40 AM

To: abutler@oakbluffsma.gov

Cc: Vincent Paquette < vpaquette@clinellc.com >; David Ford < dford@clinellc.com >

Subject: RE: AT&T Small Cell // Oak Bluffs, MA - (3) Proposed Wireless Facilities // Grant of Location - Application

**Package** 

Dear Town of Oak Bluffs Board of Selectmen,

In addition to the Grant of Location filing that was submitted on 4/2, attached please find a supplement filing letter outlining a change in address for one of the locations.

Let me know if you have any questions.

Thanks

David Ford **Centerline Communications** 508.821.6509

From: David Ford <dford@clinellc.com> Sent: Friday, April 2, 2021 1:31 PM To: abutler@oakbluffsma.gov

Cc: Vincent Paquette < vpaquette@clinellc.com >; David Ford < dford@clinellc.com >

Subject: AT&T Small Cell // Oak Bluffs, MA - (3) Proposed Wireless Facilities // Grant of Location - Application Package

Dear Town of Oak Bluffs Board of Selectmen,

In regards to AT&T's (3) proposed small cell facilities at the below referenced addresses, attached please find the Grant of Location package.

- OAKB\_002 64 Circuit Ave
- OAKB\_003 04 Massasoit Ave
- OAKB\_004 02 Pennecook Ave

Please review and let us know if you need anything further to add us to the next available agenda.

Call or email with any questions or concerns

Thanks



**David Ford** | Site Acquisition Lead – Project Manager Mobile: 508.821.6509 | Fax: 508.819.3017 dford@clinellc.com | www.centerlinecommunications.com

# ORDER FOR LOCATION FOR TELECOMMUNICATIONS WIRES AND WIRELESS ATTACHMENTS AND APPURTENANCES

By the Board of Selectmen
Of the Town of Oak Bluffs, Massachusetts,, 2021
ORDERED:
That pursuant to the federal Telecommunication Act of 1996 and Massachusetts General Laws, Chapter 166, NEW CINGULAR WIRELESS PCS, LLC ("AT&T") is hereby granted a location for and permission to construct and maintain telecommunications wires and wireless attachments and appurtenances, including fiber optic cable(s), remote nodes and pole top antennas, to be attached to Eversource utility poles, located upon, along and under the public ways within the Town of Oak Bluffs, as substantially shown on the plans filed with said petition.
The forgoing permission is subject to the following condition: the telecommunications wires and wireless attachments and appurtenances shall be installed and operated in compliance with all applicable federal, state and local laws, codes and regulations.
I hereby certify that the foregoing was adopted at a meeting of the Board of Selectmen of the Town of Oak Bluffs, Massachusetts, held on the day of, 2021.
Town Clerk

63973464 v3



# AT&T SITE ID: CRAN\_RCTB\_OAKB\_002 **64 CIRCUIT AVE** OAK BLUFFS, MA 02557





750 WEST CENTER STREET. SUITE# 301 WEST BRIDGEWATER, MA 02379





APPROVED BY

REV.	DATE	DESCRIPTION	BY
1	12/23/20	ESUES FOR CONSTRUCTION	MS
	17/14/70	STREET FOR HEIGHT	ME

CRAN\_RCTB\_OAKB\_002

SITE ADDRESS: 64 CIRCUIT AVE OAK BLUFFS, MA 02557 DUKES COUNTY

VICINITY MAP (NOT TO SCALE) SHALL IMMEDIATELY NOTIFY THE PROJECT OWNER'S REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

#### PROJECT DESCRIPTION

SHEET INDEX

SHEET

DESCRIPTION

TITLE SHEET

GENERAL NOTES KEY PLAN AND ELEVATION

EQUIPMENT DETAILS

ELECTRICAL & GROUNDING DETAILS

- INSTALLATION OF ANTENNA AND ASSOCIATED EQUIPMENT ON PROPOSED UTILITY
- THIS IS AN UNMANNED AND RESTRICTED ACCESS EQUIPMENT SITE AND WILL BE USED FOR THE TRANSMISSION OF RADIO SIGNALS FOR THE PURPOSE OF IMPROVING CELLULAR AND WIRELESS INTERNET SERVICE.

#### **DRIVING DIRECTIONS**

FROM FRAMINGHAM, MA:

REV.

HEAD NORWEST TOWARD LEGGATT McCALL CONN. TURN LEFT ONTO LEGGATT McCALL, CONN. CONTINUE ONTO BURR ST. TURN LEFT ONTO COCHITUATE RD. TAKE THE 1-90 E/MASSPIKE RAMP  **CALL 811** 

DO NOT SCALE DRAWINGS

CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND

**GENERAL NOTES** 

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF AT&T. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED, DUPLICATION AND USE BY COVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

THE FACILITY IS AN UNMANNED PRIVATE AND SECURED EQUIPMENT INSTALLATION, IT IS ONLY ACCESSED BY TRAINED TECHNICIANS FOR PERIODIC ROUTINE MAINTENANCE AND THEREFORE DOES NOT REQUIRE ANY WATER OR SANTARY SEWER SERVICE. THE FACILITY IS NOT GOVERNED BY REQUIATIONS REQUIRING PUBLIC ACCESS PER ADA REQUIREMENTS.

CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE AT&T MOBILITY REPRESENTATIVE IN WRITING OF

DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

CONSTRUCTION DRAWINGS ARE VALID FOR SIX MONTHS AFTER ENGINEER OF RECORD'S STAMPED AND SIGNED SUBMITTAL DATE LISTED HEREIN.



WWW.DIGSAFE.COM **72 HOURS PRIOR** UNDERGROUND SERVICE ALERT

PROJECT SUMMARY				
SITE ADDRESS:	64 CIRCUIT AVE OAK BLUFFS, MA 02557			
COUNTY:	DUKES			
LATITUDE:	41.454517 N			
LONGITUDE:	70.558951° W			
POLE OWNER:	EVERSOURCE			
STRUCTURE TYPE:	UTILITY POLE			
POLE NUMBER:	#19/1S			
ARCHITECT/ENGINEER:	HUDSON DESIGN GROUP LLC 45 BEECHWOOD DRIVE			

NORTH ANDOVER, MA 01845

CHECKED BY

SURMITTALS

DPH

REV.	DATE	DESCRIPTION	BY
			Н
	_		
_			
1	12/22/20	65UED FOR CONSTRUCTION	MR
	17/14/70	STREET FOR HEIGH	ME

CRAN\_RCTB\_OAKB\_002

TITLE SHEET

SHEET NUMBER T-1

#### **GENERAL NOTES**

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:

CONTRACTOR - CENTERLINE SUBCONTRACTOR - GENERAL CONTRACTOR (CONSTRUCTION) OWNER - AT&T MOBILITY

- 2. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING SUBCONTRACTOR SHALL WRIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CONTRACTOR.
- 3. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES, SUBCONTRACTOR SHALL ISSUE AND APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS, AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK, ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL, AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE PEGNILATIONS.
- 4. DRAWINGS PROVIDED HERE ARE NOT TO BE SCALED AND ARE INTENDED TO SHOW OUTLINE ONLY.
- UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES, AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
- "KITTING LIST" SUPPLIED WITH THE BID PACKAGE IDENTIFIES ITEMS THAT WILL BE SUPPLIED BY CONTRACTOR. ITEMS NOT INCLUDED IN THE BILL OF MATERIALS AND KITTING LIST SHALL BE SUPPLIED BY THE SUBCONTRACTOR.
- THE SUBCONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE
- IF THE SPECIFIED EQUIPMENT CANNOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE SUBCONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION SPACE FOR APPROVAL BY THE CONTRACTOR.
- 9. SIBECONTRACTOR SHALL DETERMINE ACTUAL ROUTING OF CONDUIT, POWER AND T1 CABLES, GROUNDING CABLES AS SHOWN ON THE POWER, GROUNDING AND TELO PLAN DRAWING, SUBCONTRACTOR SHALL UTILIZE EXISTING TRAYS AND/OR SHALL ADD NEW TRAYS AS NECESSARY, SUBCONTRACTOR SHALL CONTRIN THE ACTUAL ROUTING WITH THE CONTRACTOR.
- 10. THE SUBCONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT SUBCONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
- 11. SUBCONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COMMAIL CABLES AND OTHER TIEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- 12. SUBCONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION
- ALL CONCRETE REPAIR WORK SHALL BE DONE IN ACCORDANCE WITH AMERICAN CONCRETE INSTITUTE (ACI) 301.
- 14. ANY NEW CONCRETE NEEDED FOR THE CONSTRUCTION SHALL BE AIR-ENTRAINED AND SHALL HAVE 4000 PS STRENGTH AT 28 DAYS. ALL CONCRETE WORK SHALL BE DONE IN ACCORDANCE WITH AC 318 CODE REQUIREMENTS.
- 15. ALL STRUCTURAL STEEL WORK SHALL BE DETAILED, FABRICATED AND ERECTED IN ACCORDANCE WITH AISC SPECIFICATIONS. ALL STRUCTURAL STEEL SHALL BE ASTM A36 (Fy = 36 ks) UNLESS OTHERWISE NOTED. PIPES SHALL BE ASTM A53 TYPE E
- (Fy = 36 ks), ALL SIEEL EXPOSED TO WEATHER SHALL BE HOT DIPPED GALVANIZED. TOUCHUP ALL SCRATCHES AND OTHER MARKS IN THE FIELD AFTER STEEL IS ERECTED USING A COMPATIBLE TIME RICH PAINT
- CONSTRUCTION SHALL COMPLY WITH SPECIFICATIONS AND "GENERAL CONSTRUCTION SERVICES FOR CONSTRUCTION OF AT&T SITES."
- 17. SUBCONTRACTOR SHALL VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS PRIOR TO COMMENCING ANY WORK. ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS MUST BE VERIFIED. SUBCONTRACTOR SHALL NOTIFY THE CONTRACTOR OF ANY DISCREPANCIES PRIOR TO GROEFING MATERIAL, OR PROCEEDING WITH CONSTRUCTION.

18. APPLICABLE BUILDING CODES:

SUBCONTRACTOR'S WORK SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES AS ADOPTED BY THE LOCAL INTHORITY HAVINE JURISDICTION (AHJ) FOR THE LOCATION. THE EDITION OF THE AHJ ADOPTED CODES AND STANDARDS IN EFFECT ON THE DATE OF CONTRACT AWARD SHALL GOVERN THE DESIGN.

BUILDING CODE: MA STATE BUILDING CODE 780 CMR 9TH EDITION & IBC 2015 ELECTRICAL CODE: 2020 NATIONAL ELECTRICAL CODE (NFPA 70-2020)

SUBCONTRACTOR'S WORK SHALL COMPLY WITH THE LATEST EDITION OF THE FOLLOWING STANDARDS:

AMERICAN CONCRETE INSTITUTE (ACI) 318; BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE;

AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC)

MANUAL OF STREL CONSTRUCTION, ASD, FOURTEENTH EDITION;

TELECOMMUNICATIONS INDUSTRY ASSOCIATION (TIA) 222-H, STRUCTURAL STANDARDS FOR ANTENNA SUPPORTING STRUCTURES AND ANTENNAS.

FOR ANY CONFLICTS BETWEEN SECTIONS OF LISTED CODES AND STANDARDS REGARDING MATERIAL, METHODS OF CONSTRUCTION, OR OTHER REQUIREMENTS, THE MOST RESTRICTIVE REQUIREMENT SHALL GOVERN. WHERE THERE IS CONFLICT BETWEEN A GENERAL REQUIREMENT AND A SPECIFIC REQUIREMENT, THE SPECIFIC REQUIREMENT SHALL GOVERN.

#### **GROUNDING NOTES**

- 1. THE SUBCONTRACTOR SHALL REVIEW AND INSPECT THE EXISTING FACILITY GROUNDING SYSTEM AND LIGHTINING PROTECTION SYSTEM (AS DESIGNED AND INSTALLED) FOR STRETC COMPLIANCE WITH THE NEC (AS ADOPTED BY THE AH), THE SITE-SPECIFIC (UL. LPI, OR NFFA) LIGHTING PROTECTION CODE, AND GENERAL COMPLIANCE WITH ERICSSON AND THE ACQUIDING STANDARDS. THE SUBCONTRACTOR SHALL REPORT ANY VIOLATIONS OR ADVERSE FINDINGS TO THE CONTRACTOR SHALL REPORT ANY VIOLATIONS OR ADVERSE FINDINGS TO THE
- ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION, AND AC POWER GES'S) SHALL BE BONDED TOGETHER, AT OR BELLOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
- 3. THE SUBCONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81 STANDARDS) FOR NEW GROUND ELECTRODE SYSTEMS. THE SUBCONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
- 4. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR: STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
- EACH BTS CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 AWG STRANDED COPPER OR LARGER FOR INDOOR BTS AND #2 AWG STRANDED COPPER FOR OUTDOOR BTS.
- EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
- APPROVED ANTIOXIDANT COATINGS (I.E., CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
- 8. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO GROUND BAR.
- ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
- MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
- 11. METAL CONDUIT SHALL BE MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITHINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #8 AWG COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
- 12. ALL NEW STRUCTURES WITH A FOUNDATION AND/OR FOOTING HAVING 20 FT. OR MORE OF 1/2 IN. OR GREATER ELECTRICALLY CONDUCTIVE REINFORCING STEEL MUST HAVE IT BONDED TO THE GROUND RING USING AN EXOTHERIMIC WELD CONNECTION USING #2 AWG SOLID BARE TINNED COPPER GROUND WIRE, PER NEC 250 SD.

-	<b>€</b> at&t
	550 COCHIUATE ROAD FRAMINGHAM, MA 01701



750 WEST CENTER STREET, SUITE# 301 WEST BRIDGEWATER, MA 02379



OOD DRIVE TEL: (97



CHECKED BY:

APPROVED BY: DPH

STIDMITTALS

HV.	DATE	DESCRIPTION	BY
1	12/23/20	ISSUED FOR CONSTRUCTION	103
A	17/14/20	DOLED FOR MORE	MR

CLUSTER AND NODE NUMBER:
CRAN\_RCTB\_OAKB\_002

SITE ID:
CRAN\_RCTB\_OAKB\_002


SITE ADDRESS: 64 CIRCUIT AVE OAK BLUFFS, MA 02557 DUKES COUNTY


GENERAL NOTES

SHEET NUMBER


GN-

			ABBREVIATIONS		
AGL	ABOVE GRADE LEVEL	EQ	EQUAL	REQ	REQUIRED
AWG	AMERICAN WIRE GAUGE	GC	GENERAL CONTRACTOR	RF	RADIO FREQUENCY
88U	BATTERY BACKUP UNIT	GRC	GALVANIZED RIGID CONDUIT	TBD	TO BE DETERMINED
BTCW	BARE TINNED SOLID COPPER WIRE	MGB	MASTER GROUND BAR	TBR	TO BE REMOVED
BGR	BURKED GROUND RING	MIN	MINIMUM	TBRR	TO BE REMOVED AND REPLACED
BTS	BASE TRANSCEIVER STATION	Р	PROPOSED	TYP	TYPICAL
E	EXISTING	NTS	NOT TO SCALE	UG	UNDER GROUND
EGB	EQUIPMENT GROUND BAR	RAD	RADIATION CENTER LINE (ANTENNA)	VIF	VERIFY IN FIELD
EGR	EQUIPMENT GROUND RING	REF	RÉFERENCE		






STONEHOUSE SIGNS INC. P/N RD899
SIGN DIMENSIONS 2.5"x6.5"
TWO NOTICE STICKERS MUST BE PLACED OPPOSITE EACH OTHER ON THE ANTENNA



MOUNT PER MANUFACTURER'S SPECIFICATIONS.

A-2

ANTENNA MOUNT DETAIL
SCALE: N.T.S




MODEL	QTY.	L	W	D	WGT.
4402	2	8.0"	8.0"	4.0"	11 LBS

NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.

RRH DETAIL

SCALE: N.T.S

A-2,



NO BATTERY BACKUP OR AUXILIARY OUTLETS FOR BACKUP POWER ARE BEING PROVIDED IN THIS DESIGN

NOTE:
MOUNT PER MANUFACTURER'S SPECIFICATIONS.
EQUIPMENT CABINET DETAIL

A-2

SCALE: N.T.S

PROPOSED DIPLEXER MOUNTING BRACKET


6.9"

PROPOSED DIPLEXER COMMISCOPE MODEL COMMISCOPE MODEL FOR MODEL FO

NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.

DIPLEXER DETAIL (AS REQUIRED)

SCALE: N.T,S



RF energy emissed by this antenna may acceed the PCCs exposure finish for the general population.
STRy at least 1 feet away from the antenna.
Cell ATE7 at 600-439-3922, option 9 then 1, for help if you meet access within 1 feet.

STONEHOUSE SIGNS INC. P/N RD899
SIGN DIMENSIONS 2.5"x6.5"
TWO NOTICE STICKERS WUST BE PLACED OPPOSITE EACH OTHER ON THE ANTENNA

ANTENNA DETAIL

SCALE: N.T.S

6
A-2





750 WEST CENTER STREET, SUITE∯ 301 WEST BRIDGEWATER, MA 02379





CHECKED BY: AT

OPH

APPROVED BY:

	Si	JBMITTALS	
REV.	GATE	ESCRPTION	BY
1	12/21/20	ESIAD FOR CONSTRUCTION	MR
٨	12/14/20	STATE FOR ROADY	MR
^	12/14/20	ISSUED FOR REALIN	MR

CRAN\_RCTB\_DAKB\_002

SITE IO:
CRAN\_RCTB\_OAKB\_002


64 CIRCUIT AVE
OAK BLUFFS, MA 02557
DUKES COUNTY

SHEET TITLE

EQUIPMENT DETAILS


SHEET NUMBE

A-2





# AT&T SITE ID: CRAN\_RCTB\_OAKB\_003 4 MASSASOIT AVE. OAK BLUFFS, MA 02557



#### PROJECT DESCRIPTION

SHEET INDEX

- . INSTALLATION OF ANTENNA AND ASSOCIATED EQUIPMENT ON PROPOSED UTILITY POLE
- . THIS IS AN UNMANNED AND RESTRICTED ACCESS EQUIPMENT SITE AND WILL BE USED FOR THE TRANSMISSION OF RADIO SIONALS FOR THE PURPOSE OF IMPROVING CELLULAR AND WIRELESS INTERNET SERVICE.

#### DRIVING DIRECTIONS

SITE ADDRESS: 4 MASSASOIT AVE.
OAK BLUFFS, MA 02557

COUNTY: DUKES

 LATITUDE:
 41.452874\* N

 LONGITUDE:
 70.557325\* W

 POLE OWNER:
 EVERSOURCE

PROJECT SUMMARY

DESCRIPTION

TITLE SHEET

GENERAL NOTES

KEY PLAN AND ELEVATION

ELECTRICAL & GROUNDING DETAILS

FOLIPMENT DETAILS

STRUCTURE TYPE: UTILITY POLE
POLE NUMBER: #48/7

ARCHITECT/ENGINEER: HUDSON DESIGN GROUP LLC
45 BEECHWOOD DRIVE
NORTH ANDOVER, MA 01845

FROM FRAMINGHAM, MA:

REV.

2

2

HEAD NORWEST TOWARD LEGGATT McCALL CONN. TURN LEFT ONTO LEGGATT McCALL CONN. CONTINUE ONTO BURR ST. TURN LEFT ONTO COCHITUATE RD. TAVE THE 1—90 E/MASSPIKE RAMP TO BOSTON. MERGE ONTO 1—90 E. TAVE EXIT 14 TOWARD 1—95/PORTISMOUTH/PROVIDENCE. KEEP RIGHT AT THE FORK, FOLLOW SIGNS FOR 1—95 S/DEDHAM/PROVIDENCE AND MERGE ONTO 1—95 S. CONTINUE ONTO US—1 N. TAVE EXIT 4 FOR STATE RTE 24 S. TOWARD BROCKTON /FALL RIVER. CONTINUE ONTO MA—24 S/STATE RTE 24 S. TAVE EXIT AT THE FORM TO MERGE ONTO 1—495 S TOWARD CAPE COD. KEEP LEFT TO CONTINUE ON MA—25 E. CONTINUE ONTO MA—28 S/SENERAL MORASTHUR BLVD/MAGARTHUR BLVD. AT THE TRAFFIC CIRCLE, TAVE THE 2ND EXIT ONTO MA—28 S. AT BOURNE ROTARY S. TAVE THE TARFIC CIRCLE, TAVE THE 2ND EXIT ONTO MA—28 S. AT BOURNE ROTARY S. TAVE THE TAY THE TRAFFIC CIRCLE, TAVE THE 2ND EXIT ONTO MA—28 S. AL BOURNE ROTARY S. CONTINUE ONTO WOODS HOLD RD. TURN LEFT ONTO CRANE ST. TURN RIGHT ONTO COWDRY RD. TAVE THE WOOD HOLE — OAK BLUFFS CONTINUE STRAIGHT ONTO CAW BLUFFS CONTINUE STRAIGHT ONTO OAK BLUFFS CONT

**CALL 811** 

DO NOT SCALE DRAWINGS

CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL MIMEDIATELY NOTIFY THE PROJECT OWNER'S REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

CONSTRUCTION DRAWINGS ARE VALID FOR SIX MONTHS AFTER ENGINEER OF RECORD'S STAMPED AND SIGNED SUBMITTAL DATE LISTED HEREIN.



WWW.DIGSAFE.COM
72 HOURS PRIOR
UNDERGROUND SERVICE ALERT





750 WEST CENTER STREET, SUITE# 301 WEST BRIDGEWATER, MA 02379



DOD DRIME TEL: (978) 557-1 144 11845 FAX: (978) 336



CHECKED BY: AT

APPROVED BY: DPH

CRAN\_RCTB\_OAKB\_003

SITE ID:
CRAN\_RCTB\_OAKB\_003

5/16 ADDRESS; 4 MASSASOIT AVE. OAK BLUFFS, MA 02557 DUKES COUNTY

SHEET TITLE

TITLE SHEET

SHIFFT NUMB

T-1

#### **GENERAL NOTES**

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:

CONTRACTOR - CENTERLINE
SUBCONTRACTOR - GENERAL CONTRACTOR (CONSTRUCTION)
OWNER - AT&T MOBILITY

- PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING SUBCONTRACTOR SHALL WISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CONTRACTOR.
- 3. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REQULATIONS, AND ORDINANCES, SUBCONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REQULATIONS, AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY RECARDING THE PERFORMANCE OF THE WORK, ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL, AND LITILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE FEGULATIONS.
- 4. DRAWINGS PROVIDED HERE ARE NOT TO BE SCALED AND ARE INTENDED TO SHOW OUTLINE ONLY
- UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES, AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE PRAYMINGS.
- "KITTING LIST" SUPPLIED WITH THE BID PACKAGE IDENTIFIES ITEMS THAT WILL BE SUPPLIED BY CONTRACTOR. ITEMS NOT INCLUDED IN THE BILL OF MATERIALS AND KITTING LIST SHALL BE SUPPLIED BY THE SUBCONTRACTOR.
- THE SUBCONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- IF THE SPECIFIED EQUIPMENT CANNOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE SUBCONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION SPACE FOR APPROVAL BY THE CONTRACTOR.
- 9. SUBCONTRACTOR SHALL DETERMINE ACTUAL ROUTING OF CONDUIT, POWER AND T1 CABLES, GROUNDING AND TELO PLAN DRAWING, SUBCONTRACTOR SHALL UTILIZE EXISTING TRAYS AND/OR SHALL ADD NEW TRAYS AS NECESSARY, SUBCONTRACTOR SHALL CONFIRM THE ACTUAL ROUTING WITH THE CONTRACTOR.
- 10. THE SUBCONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAYEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT SUBCONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
- 11. SUBCONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER TIEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- 12. SUBCONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION.
- ALL CONCRETE REPAIR WORK SHALL BE DONE IN ACCORDANCE WITH AMERICAN CONCRETE INSTITUTE (ACI) 301.
- 14. ANY NEW CONCRETE NEEDED FOR THE CONSTRUCTION SHALL BE AIR—ENTRAINED AND SHALL HAVE 4000 PSI STRENGTH AT 28 DAYS, ALL CONCRETE WORK SHALL BE DONE IN ACCORDANCE WITH ACI 318 COOF REQUIREMENTS.
- 15. ALL STRUCTURAL STEEL WORK SHALL BE DETAILED, FABRICATED AND ERECTED IN ACCORDANCE WITH AISC SPECIFICATIONS, ALL STRUCTURAL STEEL SHALL BE ASTM A36 (Fy = 3.6 km) JUNIESS OTHERWISE NOTED, PIPES SHALL BE ASTM A53 TYPE E
- (Fy = 36 ksi). ALL STEEL EXPOSED TO WEATHER SHALL BE HOT DIPPED GALVANIZED. TOUCHUP ALL SCRATCHES AND OTHER MARKS IN THE FIELD AFTER STEEL IS ERECTED USING A COMPATIBLE ZINC RICH PAINT.
- 16. CONSTRUCTION SHALL COMPLY WITH SPECIFICATIONS AND "GENERAL CONSTRUCTION SERVICES FOR CONSTRUCTION OF AT&T SITES."
- 17. SUBCONTRACTOR SHALL VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS PRIOR TO COMMENCING ANY WORK, ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS MUST BE VERIFIED. SUBCONTRACTOR SHALL NOTIFY THE CONTRACTOR OF ANY DISCREPANCIES PRIOR TO ORDERING MATERIAL OR PROCEEDING WITH CONSTRUCTION.

18. APPLICABLE BUILDING CODES:

SUBCONTRACTOR'S WORK SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES AS ADOPTED BY THE LOCAL AUTHORITY HAVING JURISDICTION (AHJ) FOR THE LOCATION. THE EDITION OF THE AHJ ADOPTED CODES AND SANDARDS IN EFFECT ON THE DATE OF CONTRACT WARRD SHALL GOVERN THE DESIGN.

BUILDING CODE: MA STATE BUILDING CODE 780 CMR 9TH EDITION & IBC 2015 ELECTRICAL CODE: 2020 NATIONAL ELECTRICAL CODE (NFPA 70-2020)

SUBCONTRACTOR'S WORK SHALL COMPLY WITH THE LATEST EDITION OF THE FOLLOWING STANDARDS:

AMERICAN CONCRETE INSTITUTE (ACI) 318; BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE;

AMERICAN INSTITUTE OF STREE CONSTRUCTION (AISC)

MANUAL OF STEEL CONSTRUCTION, ASD, FOURTEENTH EDITION;

TELECOMMUNICATIONS INDUSTRY ASSOCIATION (TIA) 222-H, STRUCTURAL STANDARDS FOR ANTENNA SUPPORTING STRUCTURES AND ANTENNAS.

FOR ANY CONFLICTS BETWEEN SECTIONS OF LISTED CODES AND STANDARDS REGARDING MATERIAL METHODS OF CONSTRUCTION, OR OTHER REQUIREMENTS, THE MOST RESTRICTIVE REQUIREMENT SHALL GOVERN. WHERE THERE IS CONFLICT BETWEEN A GENERAL REQUIREMENT AND A SPECIFIC REQUIREMENT, THE SPECIFIC REQUIREMENT SHALL GOVERN.

#### **GROUNDING NOTES**

- 1. THE SUBCONTRACTOR SHALL REVIEW AND INSPECT THE EXISTING FACILITY GROUNDING SYSTEM AND LIGHTNING PROTECTION SYSTEM (AS DESIGNED AND INSTALLED) FOR STRICT COMPLIANCE WITH THE NEC (AS ADOPTED BY THE AHJ), THE SITE—SPECIFIC (UL. LPI, OR NFPA) LIGHTNING PROTECTION CODE, AND GENERAL COMPLIANCE WITH ERICSSON AND TIA GROUNDING STANDARDS. THE SUBCONTRACTOR SHALL REPORT ANY VIOLATIONS OR ADVERSE FINDINGS TO THE CONTRACTOR SHALL REPORT ANY VIOLATIONS OR ADVERSE FINDINGS TO THE
- 2. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTINING PROTECTION, AND AC POWER GES'S SHALL BE BONDED TOGETHER, AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
- 3. THE SUBCONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81 STANDARDS) FOR NEW GROUND ELECTRODE SYSTEMS. THE SUBCONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
- 4. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BITS EQUIPMENT.
- EACH BTS CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 AWG STRANDED COPPER OR LARGER FOR INDOOR BTS AND #2 AWG STRANDED COPPER FOR OUTDOOR BTS.
- EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
- APPROVED ANTIOXIDANT COATINGS (I.E., CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
- ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO GROUND BAR.
- ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BY
  USED FOR GROUNDING CONNECTIONS.
- MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE MED.
- 11. METAL CONDUIT SHALL BE MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUTLY WITH #6 AWG COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
- 12. ALL NEW STRUCTURES WITH A FOUNDATION AND/OR FOOTING HAVING 20 FT. OR MORE OF 1/2 IN. OR GREATER ELECTRICALLY CONDUCTIVE REINFORCING STEEL MUST HAVE IT BONDED TO THE GROUND RING USING AN EXOTHERMIC WELD CONNECTION USING #2 AWG SOLID BARE TINNED COPPER GROUND WIRE, PER NEC 250.50

at&t

550 COCHITUATE ROAD FRAMINGHAM, MA 01701



750 WEST CENTER STREET, SUITE# 301 WEST BRIDGEWATER, MA 02379



ECHWOOD DRIVE

DRIVE TEL: (978) 557-01645 FAX: (978) 336



CHECKED BY:

APPROVED BY:

DPH

SUBMITTALS			
REV	DATE	DESCRIPTION	BY
			Е
Ļ	03/12/21	ISSUED FOR CONSTRUCTION	MR
1		ESUED FOR CONSTRUCTION	MR.
A		ISSUED FOR REMON	MR

CLUSTER AND NODE NUMBER:
CRAN\_RCTB\_OAKB\_003

SITE ID: CRAN\_RCTB\_OAKB\_003


SITE ADDRESS:
4 MASSASOIT AVE.
OAK BLUFFS, MA 02557
DUKES COUNTY


SHEET THE


GENERAL NOTES

SHEET NUMBER

GN-1








STONEHOUSE SIGNS INC. P/N RD899
SIGN DIMENSIONS 2.5"x6.5"
TWO NOTICE STICKERS MUST BE PLACED OPPOSITE EACH OTHER ON THE ANTENNA


Call AT&T at 800-538-2822, option 9 then 3, for help if you need access within 1 feet.



NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.

ANTENNA MOUNT DETAIL
SCALE: N.T.S

4
A-2




MODEL	QTY.	L.	W	D	WGT.
4402	2	8.0*	8.0"	4.0"	11 LBS

NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.

RRH DETAIL

SCALE: N.T.S

2
A-2




39" x 15" X 23" = 7.78 CU.FT.

NO BATTERY BACKUP OR AUXILIARY OUTLETS FOR BACKUP POWER ARE BEING PROVIDED IN THIS DESIGN

NOTE:
MOUNT PER MANUFACTURER'S SPECIFICATIONS.

EQUIPMENT CABINET DETAIL


5
SCALE: N.T.S



NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.

DIPLEXER DETAIL (AS REQUIRED) SCALE: N.T.S

) 3 A-2



RF energy exercise to the several may exceed the PCC e exposure lambs for the general population.

Stay at least 1 feet away from the antenna.

Call ATET at 800-533-8522, opion 9 then 3, for help if you need access within 1 feet.

STONEHOUSE SIGNS INC. P/N RD899
SIGN DIMENSIONS 2.5"x6.5"

TWO NOTICE STICKERS MUST BE PLACED OPPOSITE EACH OTHER ON THE ANTENNA

ANTENNA DETAIL 6
SCALE: N.T.S A-2





750 WEST CENTER STREET, SUITE# 301 WEST BRIDGEWATER, MA 02379



ECHNOCO DANS | Bit (FTM 557-55) BOVER MA 91845 | FAX: (FTM 336-55)



CHECKED BY: AT

APPROVED BY: DPH

	S	JBMITTALS -	
REV.	ME	CONTRA	6X
			F
	-		F
2	03/12/21	ISSUED FOR CONSTRUCTION	MR
1	12/23/20	ASSUED FOR CONSTRUCTION	MR
A	12/14/20	ISSUED FOR REVEW	MR

CRAN\_RCTB\_OAKB\_003

CRAN\_RCTB\_OAKB\_DO3


SITE ADDRESS
4 MASSASOIT AVE.
OAK BLUFFS, MA 02557
DUKES COUNTY

SHELT TITLE

EQUIPMENT DETAILS

SHEET MANN

A-2





# AT&T SITE ID: CRAN\_RCTB\_OAKB\_004 2 PENNECOOK AVE OAK BLUFFS, MA 02557





SUITE# 301 WEST BRIDGEWATER, MA 02379



AT

DPH



CHECKED BY

APPROVED BY:

Ų.,	SUBMITTALS					
HEY	DATE	DESCRIPTION	Ţ			
			ŧ			
			ŧ			
			ŧ			
1		ESUED FOR CONSTRUCTION	Ŧ			
4.	12/16/20	COURS HER REVIEW	T			

CHISTER AND NODE NUMBER-CRAN\_RCTB\_OAKB\_004


CRAN\_RCTB\_OAKB\_004

9 PENNECOOK AVE OAK BLUFFS, MA 02557 DUKES COUNTY

SHEET TITLE

TITLE SHEET

T-1



**PROJECT SUMMARY** 

2 PENNECOOK AVE OAK BLUFFS, MA 02557

DUKES

41.452216° N

70,553572" W

EVERSOURCE

UTILITY POLE

HUDSON DESIGN GROUP LLC 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845

SITE ADDRESS:

COUNTY:

LATITUDE:

LONGITUDE:

POLE OWNER:

POLE NUMBER: ARCHITECT/ENGINEER:

STRUCTURE TYPE:

## **DRIVING DIRECTIONS**

FROM FRAMINGHAM, MA:

HEAD NORWEST TOWARD LEGGATT McCALL CONN. TURN LEFT ONTO LEGGATT McCALL CONN.

CONTINUE ONTO BURR ST. TURN LEFT ONTO COCHITUATE RD. TAKE THE 1-90 E/MASSPIKE RAMP
TO BOSTON. MERGE ONTO 1-80 E. TAKE EXIT 14 TOWARD 1-95/PORTSMOUTH/PROVIDENCE. KEP
RIGHT AT THE FORK, FOLLOW SIONS FOR 1-95 S/DEDHAM/PROVIDENCE AND MERGE ONTO 1-95
S. CONTINUE ONTO US-1 N. CONTINUE ONTO 1-93 N/US-1 N. TAKE EXIT 14.
TO MERGE ONTO 1-95 S TOWARD CAPE COD. KEP LEFT TO CONTINUE RT 24
S CONTROL PROCKTON / FALE EXIT 14.
TO MERGE ONTO 1-95 S TOWARD CAPE COD. KEP LEFT TO CONTINUE ON MA-25 E. CONTINUE ONTO MA-28 S. AT BOURNE ROTARY S, TAKE THE SIRE DIXT ONTO MA-28 S/GENERAL

MODARTHUR BLVD/MODARTHUR BLVD. AT THE TRAFFIC CIRCLE TAKE THE 2ND EXIT ONTO MA-28 S/GENERAL

MODARTHUR BLVD/MODARTHUR BLVD. AT THE TRAFFIC CIRCLE TAKE THE 2ND EXIT ONTO A-28

S. MA -28 S TURN RIGHT AND BECOMES LOCUS ST. CONTINUE ONTO WOODS HOLE RD. TURN

LEFT ONTO CRANE ST. TURN RIGHT ONTO COMBRY RD. TAKE THE WOOD HOLE — OAK BLLFFS

FERRY TO GAK BLUFFS. CONTINUE STRAGHT ONTO GAK BLLFFS AVE. TURN LEFT ONTO SEAMEN

DO NOT SCALE DRAWINGS CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE PROJECT OWNER'S REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

**GENERAL NOTES** 

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF AT&T.

ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED.

DUPLICATION AND USE BY COVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR

LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

THE FACILITY IS AN UNMANNED PRIVATE AND SECURED EQUIPMENT INSTALLATION. IT IS ONLY ACCESSED BY TRAINED TECHNICIANS FOR PERIODIC ROUTINE MAINTENANCE AND THEREFORE DOES NOT REQUIRE ANY WATER OR SANITARY SEWER SERVICE. THE FACILITY IS NOT COVERNED BY REGULATIONS REQUIRING PUBLIC ACCESS PER ADA REQUIREMENTS.

CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ATAT MOBILITY REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

4. CONSTRUCTION DRAWINGS ARE VALID FOR SIX MONTHS AFTER ENGINEER OF RECORD'S STAMPED AND SIGNED SUBMITTAL DATE LISTED HEREIN.

#### **CALL 811**



WWW.DIGSAFE.COM **72 HOURS PRIOR** UNDERGROUND SERVICE ALERT

#### **GENERAL NOTES**

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:

CONTRACTOR - CENTERLINE SUBCONTRACTOR - GENERAL CONTRACTOR (CONSTRUCTION)
OWNER - AT&T MOBILITY

- PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING SUBCONTRACTOR SHALL, VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CONTRACTOR.
- 3. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES. SUBCONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS, AND LAWFUL, ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK, ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND
- 4. DRAWINGS PROVIDED HERE ARE NOT TO BE SCALED AND ARE INTENDED TO SHOW OUTLINE
- UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES, AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED
- "KITTING LIST" SUPPLIED WITH THE BID PACKAGE IDENTIFIES ITEMS THAT WILL BE SUPPLIED BY CONTRACTOR. ITEMS NOT INCLUDED IN THE BILL OF MATERIALS AND KITTING LIST SHALL, BE SUPPLIED BY THE SUBCONTRACTOR.
- THE SUBCONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- 8. IF THE SPECIFIED EQUIPMENT CANNOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE SUBCONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION SPACE FOR APPROVAL BY THE CONTRACTOR.
- SUBCONTRACTOR SHALL DETERMINE ACTUAL ROUTING OF CONDUIT, POWER AND T1 CABLES, ROUNDING CABLES AS SHOWN ON THE POWER, GROUNDING AND ELICO PLAN DRAWING. SUBCONTRACTOR SHALL UTILIZE EXISTING TRAYS AND/OR SHALL ADD NEW TRAYS AS NECESSARY, SUBCONTRACTOR SHALL CONFIRM THE ACTUAL ROUTING WITH THE CONTRACTOR.
- THE SUBCONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT
- 11. SUBCONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- 12. SUBCONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION
- 13. ALL CONCRETE REPAIR WORK SHALL BE DONE IN ACCORDANCE WITH AMERICAN CONCRETE INSTITUTE (ACI) 301.
- 14. ANY NEW CONCRETE NEEDED FOR THE CONSTRUCTION SHALL BE AIR-ENTRAINED AND SHALL HAVE 4000 PSI STRENGTH AT 28 DAYS. ALL CONCRETE WORK SHALL BE DONE IN ACCORDANCE WITH ACI 318 CODE REQUIREMENTS.
- 15. ALL STRUCTURAL STEEL WORK SHALL BE DETAILED, FABRICATED AND ERECTED IN ACCORDANCE WITH AISC SPECIFICATIONS. ALL STRUCTURAL STEEL SHALL BE ASTM A36 (Fy = 36 ksi) UNLESS OTHERWISE NOTED, PIPES SHALL BE ASTM A53 TYPE E

(Fy = 36 ksi). ALL STEEL EXPOSED TO WEATHER SHALL BE HOT DIPPED GALVANIZED.

TOUCHUP ALL SCRATCHES AND OTHER MARKS IN THE FIELD AFTER STEEL IS ERECTED USING A COMPATIBLE ZINC RICH PAINT.

- 16. CONSTRUCTION SHALL COMPLY WITH SPECIFICATIONS AND "GENERAL CONSTRUCTION SERVICES FOR CONSTRUCTION OF AT&T SITES."
- 17. SUBCONTRACTOR SHALL VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS PRIOR TO COMMENCING ANY WORK, ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS MUST BE VERIFIED. SUBCONTRACTOR SHALL NOTIFY THE CONTRACTOR OF ANY DISCREPANCIES PRIOR TO ORDERING MATERIAL OR PROCEEDING WITH CONSTRUCTION.

18. APPLICABLE BUILDING CODES:

SUBCONTRACTOR'S WORK SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES AS ADOPTED BY THE LOCAL AUTHORITY HAVING JURISDICTION (AHJ) FOR THE LOCATION. THE EDITION OF THE AHJ ADOPTED CODES AND STANDARDS IN EFFECT ON THE DATE OF CONTRACT AWARD SHALL GOVERN THE DESIGN.

BUILDING CODE: MA STATE BUILDING CODE 780 CMR 9TH EDITION & IBC 2015 ELECTRICAL CODE: 2020 NATIONAL ELECTRICAL CODE (NFPA 70-2020)

SUBCONTRACTOR'S WORK SHALL COMPLY WITH THE LATEST EDITION OF THE FOLLOWING

AMERICAN CONCRETE INSTITUTE (ACI) 318: BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE

AMERICAN INSTITUTE OF STERI, CONSTRUCTION (AISC)

MANUAL OF STEEL CONSTRUCTION, ASD, FOURTEENTH EDITION;

TELECOMMUNICATIONS INDUSTRY ASSOCIATION (TIA) 222-H, STRUCTURAL STANDARDS FOR ANTENNA SUPPORTING STRUCTURES AND ANTENNAS.

FOR ANY CONFLICTS BETWEEN SECTIONS OF LISTED CODES AND STANDARDS REGARDING MATERIAL, METHODS OF CONSTRUCTION, OR OTHER REQUIREMENTS, THE MOST RESTRICTIVE REQUIREMENT SHALL GOVERN. WHERE THERE IS CONFLICT BETWEEN A GENERAL REQUIREMENT AND A SPECIFIC REQUIREMENT, THE SPECIFIC REQUIREMENT SHALL GOVERN.

#### **GROUNDING NOTES**

- THE SUBCONTRACTOR SHALL REVIEW AND INSPECT THE EXISTING FACILITY GROUNDING SYSTEM AND LIGHTNING PROTECTION SYSTEM (AS DESIGNED AND INSTALLED) FOR STRICT COMPLIANCE WITH THE NEC (AS ADOPTED BY THE AHJ, THE SITE—SPECIFIC (UL. LPI, OR NFPA) LIGHTING PROTECTION CODE, AND GENERAL COMPLIANCE WITH ERICSSON AND TIA GROUNDING STANDARDS. THE SUBCONTRACTOR SHALL REPORT ANY VIOLATIONS OR ADVERSE FINDINGS TO THE CONTRACTOR FOR RESOLUTION
- ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION, AND AC POWER GES'S) SHALL BE BONDED TOGETHER, AT OR BELOW GROUE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
- 3. THE SUBCONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81 STANDARDS) FOR NEW GROUND ELECTRODE SYSTEMS. THE SUBCONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT
- METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC. SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT
- 5. EACH BTS CABINET FRAME SHALL BE DIRECTLY. CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND
  WIRES. #6 AWG STRANDED COPPER OR LARGER FOR INDOOR BTS AND #2 AWG STRANDED COPPER FOR OUTDOOR BTS
- 6. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW
- APPROVED ANTIOXIDANT COATINGS (I.E., CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLITED GROWND CONNECTIONS.
- 8. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO GROUND BAR.
- ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
- 10. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE
- 11. METAL CONDUIT SHALL BE MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 AWG COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
- 12. ALL NEW STRUCTURES WITH A FOUNDATION AND/OR FOOTING HAVING 20 FT. OR MORE OF 1/2 IN. OR GREATER ELECTRICALLY CONDUCTIVE REINFORCING STEEL MUST HAVE IT BONDED TO THE GROUND RING USING AN EXOTHERMIC WELD CONNECTION USING #2 AWG SOLID BARE TINNED COPPER GROUND WIRE, PER

	at&t
550 COCHIT	HATE POAD

FRAMINGHAM, MA 01701



750 WEST CENTER STREET. SUITE# 301 WEST BRIDGEWATER, MA 02379



TBL: #78 557-5553 FAX #78 336-5586

ΑT

DPH



CHECKED BY

APPROVED BY

HEV.	BAGE	DESCRIPTION	BY
-	12/21/20	ISSUED FOR CONSTRUCTION	100
		RESERVE ALTHOUGH	MR

CLUSTER AND NOOF NUMBER-CRAN\_RCTB\_OAKB\_004


CRAN\_RCTB\_OAKB\_004 SITE ADDRESS: 2 PENNECOOK AVE OAK BLUFFS, MA 02557 DUKES COUNTY


SHEET TITLE

GENERAL NOTES

GN-1


			ABBREVIATIONS		
AGL	ABOVE GRADE LEVEL	EQ	EQUAL	REQ	REQUIRED
AWG	AMERICAN WIRE GAUGE	GC	GENERAL CONTRACTOR	RF	RADIO FREQUENCY
88u	BATTERY BACKUP UNIT	GRC	GALVANIZED RIGID CONDUIT	TBD	TO BE DETERMINED
BTCW	BARE TINNED SOLID COPPER WIRE	MGB	MASTER GROUND BAR	TBR	TO BE REMOVED
BGR	BURIED GROUND RING	MIN	MINIMUM	TBRR	TO BE REMOVED AND REPLACED
BTS	BASE TRANSCEIVER STATION	Р	PROPOSED	TYP	TYPICAL
E	EXISTING	NTS	NOT TO SCALE	UG	UNDER GROUND
EG8	EQUIPMENT GROUND BAR	RAD	RADIATION CENTER LINE (ANTENNA)	VIF	VERIFY IN FIELD
EGR	EQUIPMENT GROUND RING	REF	REFERENCE		






SIGN DIMENSIONS 2.5"x6.5"

TWO NOTICE STICKERS MUST BE PLACED OPPOSITE EACH OTHER ON THE ANTENNA



NOTE:
MOUNT PER MANUFACTURER'S SPECIFICATIONS.


**ANTENNA MOUNT DETAIL** SCALE: N.T.S A-2



MODEL	QTY.	L	W	D	WGT.
4402	2	8.0"	8.0"	4.0"	11 LBS

MOUNT PER MANUFACTURER'S SPECIFICATIONS.


RRH DETAIL SCALE: N.T.S



CABINET VOLUME: 39" x 15" X 23" = 7.78 CU.FT.

NO BATTERY BACKUP OR AUXILIARY OUTLETS FOR BACKUP POWER ARE BEING PROVIDED IN THIS DESIGN


NOTE:
MOUNT PER MANUFACTURER'S SPECIFICATIONS. **EQUIPMENT CABINET DETAIL** SCALE: N.T.S A-2



MOUNT PER MANUFACTURER'S SPECIFICATIONS.

DIPLEXER DETAIL (AS REQUIRED)

SCALE: N.T.S A-2



NOTICE RF energy emitted by this antenna may exceed the FCC's exposure limits for the general population. Stay at least 1 feet away from the antenna. Gall AT&T at 800-438-2822, option 9 then 3, for help if you need access within 1 feet.

STONEHOUSE SIGNS INC. P/N RD899 SIGN DIMENSIONS 2.5"x6.5"

TWO NOTICE STICKERS MUST BE PLACED OPPOSITE EACH OTHER ON THE ANTENNA

ANTENNA DETAIL SCALE: N.T.S

A-2/





750 WEST CENTER STREET, SUITE# 301 WEST BRIDGEWATER, MA 02379





CHECKED BY ΑŤ

APPROVED BY DPH

	SI	JBMITTALS	
H(V	IME	KSSFIN	Br
			E
	-0.000.000	AND DESCRIPTIONS	
+		DUE FOR CONSTRUCTION	PR.


CLUSTER AND NOOE NUMBERS CRAN\_RCTB\_OAKB\_004

CRAN\_RCTB\_OAKB\_004

2 PENNECOOK AVE OAK BLUFFS, MA 02557 OUKES COUNTY

EQUIPMENT DETAILS

SHEET NUMBER



# STRUCTURAL ANALYSIS REPORT

For

# CRAN\_RCTB\_OAKB\_002

64 Circuit Avenue Oak Bluffs, MA 02557

# **Equipment Mounted on Proposed Utility Pole**



## Prepared for:





Dated: December 18, 2020

Prepared by:



HUDSON Design Group LLC

45 Beechwood Drive North Andover, MA 01845 Phone: (978) 557-5553

www.hudsondesiangroupllc.com



## **SCOPE OF WORK:**

Hudson Design Group LLC (HDG) has been authorized by AT&T to conduct a structural evaluation of the proposed utility pole supporting the proposed AT&T equipment.

This report represents this office's findings, conclusions and recommendations pertaining to the support of the proposed AT&T equipment listed below.

This office conducted an on-site visual survey of the above areas on June 23, 2020. Attendees included Patrick Barrett (HDG – Field Technician).

## **CONCLUSION SUMMARY:**

Based on our evaluation, we have determined that the proposed pole <u>is in conformance</u> with the National Electric Safety Code 2017 (NESC). <u>The utility pole structure is rated at 74.0%</u>.

#### APPURTENANCES CONFIGURATION:

Appurtenances	Elev.	Mount
(1) GQ2410-06621 Antenna	33'-5"	Top of Pole Top Shroud
(3) AIR1281 Antenna	30'-7"	Pole Top Shroud
(1) Demarc Box	17'-0"	Side of Wood Pole
(1) Equipment Cabinet	13'-0"	Side of Wood Pole
(1) Disconnect Switch	10'-3"	Side of Wood Pole
(1) Elec. Meter	8'-9"	Side of Wood Pole

#### **ANALYSIS RESULTS SUMMARY:**

Component	Max. Stress Ratio	Elev. of Component (ft.)	Pass/Fail
SYP 2 (Proposed)	74.0%	0 - 29.5	PASS



## DESIGN CRITERIA:

National Electric Safety 9th Edition.	Code 2017 (NESC)	) and the Massachusetts State Building Code
Wind		
City/Town:	Oak Bluffs	
County:	Dukes	
NESC Rule	Rule 250B	NESC Section 25
Construction Grade	С	NESC Section 25
Wind Load:	39.53 mph	NESC Table 230-2
Ice		
Loading District	Heavy	NESC Figure 250-1
Radial Ice Thickness:	0.50 in	NESC Table 230-1

- 1. Approximate height above grade to center of the proposed Galtronics antenna: 33'-5" +/-
- 2. Approximate height above grade to center of the proposed Ericsson antennas: 30'-7''+/-

<sup>\*</sup>Calculations and referenced documents are attached.



#### PROPOSED STRUCTURE:

The proposed 29'-6" +/- utility pole is assumed to be Southern Yellow Pine class 2 (Fb = 8000 psi) with an 11.62" diameter base. If field conditions differ from what is assumed in this report, then the engineer of record is to be notified as soon as possible.

#### ANTENNA SUPPORT RECOMMENDATIONS:

- The new Galtronics antenna is proposed to be installed on the proposed pole top shroud using thru bolts.
- The new Ericsson antennas are proposed to be installed within the proposed pole top shroud secured to the wood pole using a low-profile pole top kit.

#### **EQUIPMENT SUPPORT RECOMMENDATIONS:**

The new equipment is proposed to be installed on the wood pole using the approved manufacturer's mounts.

#### Limitations and assumptions:

- 1. Reference the latest HDG construction drawings for all the equipment locations details.
- 2. Mount all equipment per manufacturer's specifications.
- 3. All structural members and their connections are assumed to be in good condition and are free from defects with no deterioration to its member capacities. Contractor to perform pre-inspection prior to construction.
- 4. All antennas and waveguide cables are assumed to be properly installed and supported as per the manufacturer requirements.
- 5. HDG is not responsible for any modifications completed prior to and hereafter which HDG was not directly involved.
- 6. If field conditions differ from what is assumed in this report, then the engineer of record is to be notified as soon as possible.
- 7. HDG did not perform any geotechnical analysis / or / investigation. Soil Information is unknown.



# FIELD PHOTOS:




**Photo 1:** Sample photo illustrating the existing wood pole (to be removed and replaced).



**Calculations** 

Pole Num:	Proposed Pole	Pole Length / Class:	35 / 2	Code:	NESC	Structure Type:	Deadend
Pole Number	Proposed Pole	Species:	SOUTHERN PINE	NESC Rule:	Rule 250B	Status	Guy Wires Adequate
Site Name	cRAN_RCTB_OAKB_002	Setting Depth (ft):	5.5	Construction Grade:	С	Pole Strength Fac	tor: <b>0.85</b>
Site Address	64 Circuit Avenue	G/L Circumference (in)	36.50	Loading District:	Heavy	Transverse Wind	LF: 1.75
City, State	Oak Bluffs, MA	G/L Fiber Stress (psi):	8,000	Ice Thickness (in):	0.50	Wire Tension LF:	1.30
Zip Code	02557	Allowable Stress (psi):	6,800	Wind Speed (mph):	39.53	Vertical LF:	1.90
Designed By	KM	Fiber Stress Ht. Reduc	: No	Wind Pressure (psf):	4.00		
Latitude:		41.454517° N L	ongitude:		70.558951° W	Elevation:	78'



Pole Capacity Utiliza	tion (%)	Height (ft)	Wind Angle (deg)
Maximum	74.0	0.0	84.8
Groundline	74.0	0.0	84.8
Vertical	1.4	18.3	263.0

Pole Moments (ft-lb)		Load Angle (deg)	Wind Angle (deg)
Max Cap Util	63,663	47.9	84.8
Groundline	63,663	47.9	84.8
GL Allowable	87,248		

Guy System Component Summary				Load From Angle o			aximum Load oad Applied
Description	Lead Length (ft)	Lead Angle (deg)	Height (ft)	Nominal Capacity (%)	Wind Angle (deg)	Max* Load Capacity (%)	Wind Angle (deg)
► Anchor	103.0	13.0		0.0	84.8	0.0	0.0
EHS 3/8 (Span/Head)			18.5	0.0	84.8	0.0	0.0
▶ Single Helix Anchor	10.0	153.0		21.3	84.8	28.3	300.0
<ul> <li>EHS 3/8 (Sidewalk)</li> </ul>			18.5	30.7	84.8	40.8	300.0
○ Sidewalk Strut	10.0	153.0	10.1	81.5	84.8	98.5	300.0
		System Capaci	ity Summary:	Adeq	uate	At Ca	oacity

Groundline Load Summary	/ - Reporting A	Angle Mode: L	oad - Reportir	ng Angle: 47.9	0					
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
Powers	1,569	45.4	35,899	56.4	41.2	2,995	148	1	2,997	44.1
Comms	1,503	43.5	28,060	44.1	32.2	2,341	156	1	2,343	34.5
GuyBraces	132	3.8	-5,084	-8.0	-5.8	-793	4,204	40	-754	-11.1
GenericEquipments	116	3.4	2,783	4.4	3.2	232	785	7	240	3.5
Pole	135	3.9	1,950	3.1	2.2	163	1,778	17	179	2.6
Risers	3	0.1	56	0.1	0.1	5	56	1	5	0.1
Insulators	0	0.0	0	0.0	0.0	0	19	0	0	0.0
Pole Load	3,457	100.0	63,663	100.0	73.0	4,943	7,146	67	5,010	73.7
Pole Reserve Capacity			23,585		27.0	1,857			1,790	26.3

Load Summary by Owner -	oad Summary by Owner - Reporting Angle Mode: Load - Reporting Angle: 47.9°													
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)				
Proposed	3,191	92.3	66,797	104.9	76.6	5,573	1,165	11	5,584	82.1				
Existing	132	3.8	-5,084	-8.0	-5.8	-793	4,204	40	-754	-11.1				
Pole	135	3.9	1,950	3.1	2.2	163	1,778	17	179	2.6				
Totals:	3,457	100.0	63,663	100.0	73.0	4,943	7,146	67	5,010	73.7				

**Detailed Load Components:** 

Power		Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Secondary	DUPLEX 1/0	Proposed	24.45	6.79	0.9540		0.260	103.0	13.0	103.0			-5	217	212
Overlashed Bundle	10M	Proposed	24.50	6.79	0.3060	1.27	0.165	103.0	13.0	103.0	1,438	32,473	-5	564	33,032
											Totals:	32,473	-10	781	33,244

Comm			eight Hoi (ft) Offs (ir	set	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Overlashed Bundle 6	SM P	Proposed	20.00	7.07	0.2420	1.13	0.104	103.0	13.0	103.0	1,375	25,357	-4	461	25,813

Fiber TELE 1.0 Proposed 19.95 7.07 1.0000 0.400 103.0 13.0 103.0 -7 178 171 Totals: 25,357 -11 639 25,984

GenericEqui	pment	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Cylinder	Top Shroud	Proposed	32.20	0.19	0.0	0.0	145.00	62.50	-	16.00		-3	1,084	1,081
Cylinder	Galtronics Antenna	Proposed	33.40	0.19	180.0	0.0	19.00	24.70		10.00		0	268	267
Box	Ericsson Antenna	Proposed	30.60	0.19	180.0	0.0	18.00	11.00	5.00		8.00	0	100	99
Box	Ericsson Antenna	Proposed	30.60	0.19	180.0	0.0	18.00	11.00	5.00		8.00	0	100	99
Box	Ericsson Antenna	Proposed	30.60	0.19	180.0	0.0	18.00	11.00	5.00	_	8.00	0	100	99
Box	Fiber Demarc	Proposed	17.00	6.45	35.0	0.0	3.00	12.30	3.40		3.00	3	35	37
Box	Equipment Cabinet	Proposed	13.00	14.00	35.0	0.0	160.00	39.00	18.00		15.00	299	427	726
Box	Disconnect Switch	Proposed	10.25	7.27	35.0	0.0	17.00	12.60	4.20		8.80	17	54	71
Box	Elec. Meter	Proposed	8.75	7.77	35.0	0.0	15.00	19.00	5.00		10.00	16	80	96
											Totals:	330	2,247	2,577

Riser		Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (în)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
2" U-Guard 90.0° H:29.5	2" U-Guard	Proposed	29.50	5.90	90.0	90.0	29.50	354.00	2.00	2.00	354.00	9	43	52
											Totals:	9	43	52

Insulator		Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Bolt	Three Bolt	Proposed	24.50	0.00	310.0	220.0	5.00	3.00	0.10	0	0	0
Bolt	Three Bolt	Proposed	20.00	0.00	310.0	220.0	5.00	3.00	0.10	0	0	0
									Totals:	0	0	0

Guy Wire and Brace		Owner	Attach Height (ft)	End Height (ft)	Lead/Span Length (ft)	Wire Diameter (in)	Percent Solid (%)	Lead Angle (deg)	Incline Angle (deg)	Wire Weight (lbs/ft)	Rest Length (ft)	Stretch Length (in)
EHS 3/8	Span/Head	Existing	18.50	18.50	103.00	0.375	75.00	13.0	0.0	0.273	100.26	0.00
EHS 3/8	Sidewalk	Existing	18.50	0.00	10.00	1.38	75.00	153.0	39.8	0.273	26.87	0.05

Guy Wire and Bra (Loads and Reac		Elastic Modulus (psi)	Rated Tensile Strength (lbs)	Guy Strength Factor	Allowable Tension (lbs)	Initial Tension (lbs)	Loaded Tension* <sup>2</sup> (lbs)	Maximum Tension² (lbs)	Applied Tension <sup>3</sup> (lbs)	Vertical Load (lbs)	Shear Load In Guy Dir (Ibs)	Shear Load At Report Angle (lbs)	Moment at GL³ (ft-lb)
EHS 3/8	Span/Head	2.30e+7	15,400	0.90	13,860	700	0	0	0	0	0	0	431
EHS 3/8	Sidewalk	2.30e+7	15,400	0.90	13,860	700	5,657	5,143	4,257	2,723	3,273	-850	-5,874
									Totals:	2,723	3,273	-850	-5,443

Anchor/Rod Load Summary	Owner	Rod Length AGL (in)	Lead Length (ft)	Lead Angle (deg)	Strength of Assembly (lbs)	Anchor/Rod Strength Factor	Allowable Load (lbs)	Max Load² (lbs)	Load at Pole MCU <sup>3</sup> (lbs)	Max Required Capacity <sup>2</sup> (%)
Anchor	Existing	30.00	103.00	13.0	20,000	1.00	20,000	0	0	0.0
Single Helix Anchor	Existing	18.00	10.00	153.0	20,000	1.00	20,000	5,657	4,257	28.3

Pole Buckl	ing												
Buckling Constant	Buckling Column Height* (ft)	Buckling Section Height (% Buckling Col. Hgt.)	Buckling Section Diameter (in)	Minimum Buckling Diameter at GL (in)	Diameter at Tip (in)	Diameter at GL (in)	Modulus of Elasticity (psi)	Pole Density (pcf)	Ice Density (pcf)	Pole Tip Height (ft)	Buckling Load Capacity at Height (lbs)	Buckling Load Applied at Height (lbs)	Buckling Load Factor of Safety
0.71	18.33	32.94	10.87	4.00	7.96	11.62	2.13e+6	60.00	57.00	29.50	506,292	5104.54	71.43


# STRUCTURAL ANALYSIS REPORT

For

# CRAN\_RCTB\_OAKB\_003

11 Massasoit Avenue Oak Bluffs, MA 02557

# **Equipment Mounted on Proposed Utility Pole**



Prepared for:





Dated: December 23, 2020

Prepared by:



**HUDSON** Design Group LLC

45 Beechwood Drive North Andover, MA 01845 Phone: (978) 557-5553 www.hudsondesigngroupllc.com



#### **SCOPE OF WORK:**

Hudson Design Group LLC (HDG) has been authorized by AT&T to conduct a structural evaluation of the proposed utility pole supporting the proposed AT&T equipment.

This report represents this office's findings, conclusions and recommendations pertaining to the support of the proposed AT&T equipment listed below.

This office conducted an on-site visual survey of the above areas on June 23, 2020. Attendees included Patrick Barrett (HDG – Field Technician).

## **CONCLUSION SUMMARY:**

Based on our evaluation, we have determined that the proposed pole <u>is in conformance</u> with the National Electric Safety Code 2017 (NESC). <u>The utility pole structure is rated at 88.2%.</u>

## APPURTENANCES CONFIGURATION:

Appurtenances	Elev.	Mount Top of Pole Top Shroud		
(1) GQ2410-06621 Antenna	37'-11"			
(3) AIR1281 Antennas	35'-1"	Pole Top Shroud		
(1) Demarc Box	17'-0"	Side of Wood Pole		
(1) Equipment Cabinet	13'-0"	Side of Wood Pole		
(1) Disconnect Switch	10'-3"	Side of Wood Pole		
(1) Elec. Meter	8'-9"	Side of Wood Pole		

#### **ANALYSIS RESULTS SUMMARY:**

Component	Max. Stress Ratio	Elev. of Component (ft.)	Pass/Fail	
SYP 2 (Proposed)	88.2%	0 – 34.0	PASS	



## **DESIGN CRITERIA:**

National Electric Safety Code 2017 (NESC) and the Massachusetts State Building Code 9th Edition.					
Wind					
City/Town:	Oak Bluffs				
County:	Dukes				
NESC Rule	Rule 250B	NESC Section 25			
Construction Grade	С	NESC Section 25			
Wind Load:	39.53 mph	NESC Table 230-2			
Ice					
Loading District	Heavy	NESC Figure 250-1			
Radial Ice Thickness:	0.50 in	NESC Table 230-1			

- 1. Approximate height above grade to center of the proposed Galtronics antenna: 37'-11" +/-
- 2. Approximate height above grade to center of the proposed Ericsson antennas: 35'-1" +/-

\*Calculations and referenced documents are attached.



#### PROPOSED STRUCTURE:

The proposed 34'-0" +/- utility pole is assumed to be Southern Yellow Pine class 2 (Fb = 8000 psi) with a 12.25" diameter base. If field conditions differ from what is assumed in this report, then the engineer of record is to be notified as soon as possible.

#### ANTENNA SUPPORT RECOMMENDATIONS:

- The new Galtronics antenna is proposed to be installed on the proposed pole top shroud using thru bolts.
- The new Ericsson antennas are proposed to be installed within the proposed pole top shroud secured to the wood pole using a low-profile pole top kit.

#### **EQUIPMENT SUPPORT RECOMMENDATIONS:**

The new equipment is proposed to be installed on the wood pole using the approved manufacturer's mounts.

## <u>Limitations and assumptions:</u>

- 1. Reference the latest HDG construction drawings for all the equipment locations details.
- 2. Mount all equipment per manufacturer's specifications.
- 3. All structural members and their connections are assumed to be in good condition and are free from defects with no deterioration to its member capacities. Contractor to perform pre-inspection prior to construction.
- 4. All antennas and waveguide cables are assumed to be properly installed and supported as per the manufacturer requirements.
- HDG is not responsible for any modifications completed prior to and hereafter which HDG was not directly involved.
- 6. If field conditions differ from what is assumed in this report, then the engineer of record is to be notified as soon as possible.
- 7. HDG did not perform any geotechnical analysis / or / investigation. Soil Information is unknown.



## FIELD PHOTOS:





Photo 1: Sample photo illustrating the existing wood pole (to be removed and replaced).



**Calculations** 

Pole Num:	Proposed Pole	Pole Length / Class:	40 / 2	Code:	NESC	Structure Type:	Unguyed Tangent
Pole Number	Proposed Pole	Species:	SOUTHERN PINE	NESC Rule:	Rule 250B	Status	Unguyed
Site Name	cRAN_RCTB_OAKB_003	Setting Depth (ft):	6.0	Construction Grade:	С	Pole Strength Factor:	0.85
Site Address	1 1 Massasoit Avenue	G/L Circumference (in	): <b>38.48</b>	Loading District:	Heavy	Transverse Wind LF:	1.75
City, State	Oak Bluffs, MA	G/L Fiber Stress (psi):	8,000	Ice Thickness (in):	0.50	Wire Tension LF:	1.00
Zip Code	02557	Allowable Stress (psi):	6,800	Wind Speed (mph):	39.53	Vertical LF:	1.90
Designed By	KM	Fiber Stress Ht. Reduc	: No	Wind Pressure (psf):	4.00		
Latitude:		41.452877° N L	.ongitude:		70.557324° W	Elevation:	30'



Pole Capacity Utiliza	tion (%)	Height (ft)	Wind Angle (deg)
Maximum	88.2	0.0	41.2
Groundline	88.2	0.0	41.2
Vertical	8.7	21.0	41.2

Pole Moments (ft-lb)		Load Angle (deg)	Wind Angle (deg)
Max Cap Util	89,480	33.6	41.2
Groundline	89,480	33.6	41.2
GL Allowable	102,231		

Groundline Load Summar	y - Reporting A	ngle Mode: L	oad - Reportir	g Angle: 33.6	0					
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
Powers	717	18.4	20,857	23.3	20.4	1,364	570	5	1,369	20.1
Comms	2,821	72.4	61,145	68.3	59.8	3,999	1,356	12	4,010	59.0
GenericEquipments	147	3.8	3,654	4.1	3.6	239	785	7	246	3.6
Pole	199	5.1	3,505	3.9	3.4	229	2,190	19	248	3.6
Risers	14	0.4	311	0.4	0.3	20	65	1	21	0.3
Insulators	0	0.0	9	0.0	0.0	1	49	0	1	0.0
Pole Load	3,898	100.0	89,480	100.0	87.5	5,852	5,016	43	5,894	86.7
Pole Reserve Capacity			12,751		12.5	949			906	13.3

Load Summary by Owner -	Reporting An	gle Mode: Loa	ad - Reporting	Angle: 33.6°						
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
Existing	2,869	73.6	69,566	77.7	68.1	4,549	1,678	14	4,563	67.1
Proposed	831	21.3	16,409	18.3	16.1	1,073	1,147	10	1,083	15.9
Pole	199	5.1	3,505	3.9	3.4	229	2,190	19	248	3.6
Totals:	3,898	100.0	89,480	100.0	87.5	5,852	5,016	43	5,894	86.7

Detailed Load Components:

Power		Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Secondary	DUPLEX 1/0	Existing	28.11	6.60	0.9540		0.260	103.0	108.0	103.2			44	551	595
Secondary	DUPLEX 1/0	Existing	28.21	6.60	0.9540		0.260	103.0	108.0	103.2			44	553	597
Secondary	DUPLEX 1/0	Existing	28.11	6.60	0.9540		0.260	87.0	332.0	87.1			37	432	470
Secondary	DUPLEX 1/0	Existing	28.21	6.60	0.9540		0.260	87.0	332.0	87.1			37	434	471
Secondary	TRIPLEX 1/0	Existing	27.94	27.17	1.0300	0.50	0.399	32.0	183.0	32.0	336	-7,494	34	166	-7,293
Overlashed Bundle	10M	Existing	28.16	6.60	0.3060	2.87	0.165	103.0	108.0	103.2	1,039	8,004	39	1,313	9,356
Overlashed Bundle	10M	Existing	28.16	6.60	0.3060	1.89	0.165	87.0	332.0	87.1	1,145	15,597	33	1,031	16,661
											Totals:	16,107	270	4,480	20,857

Comm	Owner Heigh (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
------	---------------------	--------------------------	---------------------------	-------------------------------	-----------------------------	-----------------------------	------------------------	------------------------	------------------	-------------------------------	------------------------------	----------------------------	-----------------------------

Telco	TELE 1.0	Existing	22.00	7.24	1.0000	2.01	0.400	87.0	332.0	87.1	1,210	12,876	67	934	13,877
Overlashed Bundle	1/4" EHS	Existing	23.00	7.17	0.2500	2.80	0.121	103.0	108.0	103.2	979	6,152	41	1,038	7,231
CATV	CATV .75	Existing	22.95	7.17	1.0700		0.900	103.0	108.0	103.2			87	415	502
CATV	CATV .50	Existing	22.65	30.42	0.5700	0.50	0.600	32.0	188.0	32.0	305	-6,001	19	78	-5,904
Overlashed Bundle	1/4" EHS	Existing	23.00	7.17	0.2500	1.78	0.121	87.0	332.0	87.1	1,091	12,143	35	815	12,992
CATV	CATV .75	Existing	22.95	7.17	1.0700		0.900	87.0	332.0	87.1			73	326	399
Telco	TELE 1.0	Existing	21.33	7.28	1.0000	2.96	0.400	103.0	108.0	103.2	803	4,684	67	1,154	5,905
Telco	TELE 1.0	Existing	21.33	7.28	1.0000	2.01	0.400	87.0	332.0	87.1	1,210	12,484	57	905	13,446
Telco	TELE 1.0	Existing	21.33	7.28	1.0000	2.96	0.400	103.0	108.0	103.2	803	4,684	-9	1,154	5,829
Telco	TELE 1.0	Existing	21.33	7.28	1.0000	0.51	0.400	32.0	185.0	32.0	304	-5,684	-6	115	-5,576
Overlashed Bundle	6M	Proposed	18.00	7.49	0.2420	1.86	0.104	87.0	332.0	87.1	781	6,800	34	623	7,456
Fiber	TELE 1.0	Proposed	17.95	7.49	1.0000		0.400	87.0	332.0	87.1			49	240	290
Overlashed Bundle	6M	Proposed	18.00	7.49	0.2420	2.85	0.104	103.0	108.0	103.2	711	3,500	40	794	4,334
Fiber	TELE 1.0	Proposed	17.95	7.49	1.0000		0.400	103.0	108.0	103.2			58	306	365
											Totals:	51,635	613	8,897	61,145

GenericEquip	ment	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Cylinder	Top Shroud	Proposed	36.70	0.19	0.0	0.0	145.00	62.50	-	16.00		-4	1,798	1,795
Cylinder	Galtronics Antenna	Proposed	37.90	0.19	180.0	0.0	19.00	24.70	_	10.00		0	444	444
Box	Ericsson Antenna	Proposed	35.10	0.19	180.0	0.0	18.00	11.00	5.00		8.00	0	218	218
Box	Ericsson Antenna	Proposed	35.10	0.19	180.0	0.0	18.00	11.00	5.00		8.00	0	218	218
Box	Ericsson Antenna	Proposed	35.10	0.19	180.0	0.0	18.00	11.00	5.00		8.00	0	218	218
Box	Fiber Demarc	Proposed	17.00	6.75	140.0	0.0	3.00	12.30	3.40		3.00	-1	55	55
Box	Equipment Cabinet	Proposed	13.00	14.30	140.0	0.0	160.00	39.00	18.00		15.00	-104	710	606
Box	Disconnect Switch	Proposed	10.25	7.58	140.0	0.0	17.00	12.60	4.20		8.80	-6	45	39
Box	Elec. Meter	Proposed	8.75	8.07	140.0	0.0	15.00	19.00	5.00	-	10.00	-6	68	62
											Totals:	-122	3,776	3,654

Riser		Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
2" U-Guard 200.0° H:34.0	2" U-Guard	Proposed	34.00	6.25	200.0	200.0	34.00	408.00	2.00	2.00	408.00	-17	328	311
											Totals:	-17	328	311

Insulator		Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Spool	Spool 2.5"	Existing	28.16	0.00	40.0	310.0	1.00	2.50	2.12	0	7	7
Bolt	Single Bolt	Existing	22.00	0.00	40.0	310.0	5.00	3.00	0.10	0	0	0
Bolt	Three Bolt	Existing	23.00	0.00	40.0	310.0	5.00	3.00	0.10	0	0	0
Bolt	Single Bolt	Existing	21.33	0.00	0.0	0.0	5.00	3.00	0.10	0	0	0
J-Hook	J-Hook	Existing	21.33	0.00	130.0	130.0	5.00	3.00	0.10	0	0	0
Bolt	Three Bolt	Proposed	18.00	0.00	40.0	310.0	5.00	3.00	0.10	0	0	0
									Totals:	0	9	9

Pole Buckli	ing												
Buckling Constant	Buckling Column Height* (ft)	Buckling Section Height (% Buckling Col. Hgt.)	Buckling Section Diameter (in)	Minimum Buckling Diameter at GL (in)	Diameter at Tip (in)	Diameter at GL (in)	Modulus of Elasticity (psi)	Pole Density (pcf)	Ice Density (pcf)	Pole Tip Height (ft)	Buckling Load Capacity at Height (lbs)	Buckling Load Applied at Height (lbs)	Buckling Load Factor of Safety
2.00	20.98	33.24	11.37	6.65	7.96	12.25	2.13e+6	60.00	57.00	34.00	57,772	576.51	11.49

## STRUCTURAL ANALYSIS REPORT

For

# CRAN\_RCTB\_OAKB\_004

2 Pennecook Avenue Oak Bluffs, MA 02557

# **Equipment Mounted on Existing Utility Pole**



### Prepared for:





Dated: December 21, 2020

Prepared by:



**HUDSON**Design Group LLC

45 Beechwood Drive North Andover, MA 01845 Phone: (978) 557-5553 www.hudsondesigngrouplic.com





#### **SCOPE OF WORK:**

Hudson Design Group LLC (HDG) has been authorized by AT&T to conduct a structural evaluation of the existing utility pole supporting the proposed AT&T equipment.

This report represents this office's findings, conclusions and recommendations pertaining to the support of the proposed AT&T equipment listed below.

This office conducted an on-site visual survey of the above areas on June 23, 2020. Attendees included Patrick Barrett (HDG – Field Technician).

#### **CONCLUSION SUMMARY:**

Based on our evaluation, we have determined that the existing pole <u>is in conformance</u> with the National Electric Safety Code 2017 (NESC). <u>The utility pole structure is rated at 91.2%.</u>

#### APPURTENANCES CONFIGURATION:

Appurtenances	Elev.	Mount
(1) GQ2410-06621 Antenna	32'-3"	Top of Pole Top Shroud
(3) AIR1281 Antennas	29'-5"	Pole Top Shroud
(1) Demarc Box	17'-0"	Side of Wood Pole
(1) Equipment Cabinet	13'-0"	Side of Wood Pole
(1) Disconnect Switch	10'-3"	Side of Wood Pole
(1) Elec. Meter	8'-9"	Side of Wood Pole

#### **ANALYSIS RESULTS SUMMARY:**

Component	Max. Stress Ratio	Elev. of Component (ft.)	Pass/Fail
SYP 5 (Existing)	91.2%	0 - 28.3	PASS



#### **DESIGN CRITERIA:**

National Electric Safety 9th Edition.	Code 2017 (NESC)	) and the Massachusetts State Building Code
Wind		
City/Town:	Oak Bluffs	
County:	Dukes	
NESC Rule	Rule 250B	NESC Section 25
Construction Grade	С	NESC Section 25
Wind Load:	39.53 mph	NESC Table 230-2
Ice		
Loading District	Heavy	NESC Figure 250-1
Radial Ice Thickness:	0.50 in	NESC Table 230-1

- 1. Approximate height above grade to center of the proposed Galtronics antenna: 32'-3" +/-
- 2. Approximate height above grade to center of the proposed Ericsson antennas: 29'-5" +/-

<sup>\*</sup>Calculations and referenced documents are attached.



#### **EXISTING STRUCTURE:**

The existing 28'-4" +/- utility pole is assumed to be Southern Yellow Pine class 5 (Fb = 8000 psi) with a 10" diameter base. If field conditions differ from what is assumed in this report, then the engineer of record is to be notified as soon as possible.

#### **ANTENNAS SUPPORT RECOMMENDATIONS:**

- The new Galtronics antenna is proposed to be installed on the proposed pole top shroud using thru bolts.
- The new Ericsson antennas are proposed to be installed within the proposed pole top shroud secured to the wood pole using a low-profile pole top kit.

#### **EQUIPMENT SUPPORT RECOMMENDATIONS:**


The new equipment is proposed to be installed on the wood pole using the approved manufacturer's mounts.

#### Limitations and assumptions:

- Reference the latest HDG construction drawings for all the equipment locations details.
- 2. Mount all equipment per manufacturer's specifications.
- 3. All structural members and their connections are assumed to be in good condition and are free from defects with no deterioration to its member capacities. Contractor to perform pre-inspection prior to construction.
- 4. All antennas and waveguide cables are assumed to be properly installed and supported as per the manufacturer requirements.
- 5. HDG is not responsible for any modifications completed prior to and hereafter which HDG was not directly involved.
- 6. If field conditions differ from what is assumed in this report, then the engineer of record is to be notified as soon as possible.
- 7. HDG did not perform any geotechnical analysis / or / investigation. Soil Information is unknown.



## FIELD PHOTOS:





**Photo 1:** Sample photo illustrating the existing wood pole.



**Calculations** 

Pole Num:	Pole #63/2	Pole Length / Class:	35 / 5	Code:	NESC	Structure Type:	Deadend
Pole Number	Pole #63/2	Species: SOL	JTHERN PINE	NESC Rule:	Rule 250B	Status	Unguyed
Site Name	cRAN_RCTB_OAKB_004	Setting Depth (ft):	6.67	Construction Grade:	С	Pole Strength Factor:	0.85
Site Address	2 Pennecook Avenue	G/L Circumference (in):	29.00	Loading District:	Heavy	Transverse Wind LF:	1.75
City, State	Oak Bluffs, MA	G/L Fiber Stress (psi):	8,000	Ice Thickness (in):	0.50	Wire Tension LF:	1.30
Zip Code	02557	Allowable Stress (psi):	6,800	Wind Speed (mph):	39.53	Vertical LF:	1.90
Designed By	KM	Fiber Stress Ht. Reduc:	No	Wind Pressure (psf):	4.00		
Latitude:		41.452216° N Long	itude:		70.553572° W	Elevation:	8'





Pole Capacity Utiliza	tion (%)	Height (ft)	Wind Angle (deg)
Maximum	91.2	0.0	167.9
Groundline	91.2	0.0	167.9
Vertical	12.4	19.6	167.9

Pole Moments (ft-lb)		Load Angle (deg)	Wind Angle (deg)
Max Cap Util	39,706	168.8	167.9
Groundline	39,706	168.8	167.9
GL Allowable	43,759		

Groundline Load Summar	y - Reporting A	Angle Mode: L	oad - Reportin	ng Angle: 168.	8°					
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
Powers	828	46.1	20,938	52.7	47.9	3,232	214	3	3,235	47.6
Comms	567	31.5	11,992	30.2	27.4	1,851	146	2	1,853	27.3
GenericEquipments	210	11.7	3,332	8.4	7.6	514	813	12	526	7.7
Pole	120	6.7	1,742	4.4	4.0	269	948	14	283	4.2
Streetlights	40	2.2	1,107	2.8	2.5	171	114	2	173	2.5
Risers	31	1.8	594	1.5	1.4	92	54	1	93	1.4
Insulators	0	0.0	1	0.0	0.0	0	19	0	0	0.0
Pole Load	1,796	100.0	39,706	100.0	90.7	6,129	2,308	34	6,164	90.6
Pole Reserve Capacity			4,053		9.3	671			636	9.4

Load Summary by Owner	- Reporting An	gle Mode: Lo	ad - Reporting	Angle: 168.8	•					
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
Exisitng	926	51.5	22,340	56.3	51.1	3,449	366	5	3,454	50.8
Proposed	751	41.8	15,624	39.4	35.7	2,412	994	15	2,427	35.7
Pole	120	6.7	1,742	4.4	4.0	269	948	14	283	4.2
Totals:	1,796	100.0	39,706	100.0	90.7	6,129	2,308	34	6,164	90.6

**Detailed Load Components:** 

Power		Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Secondary	DUPLEX 1/0	Exisitng	24.95	5.36	0.9540		0.260	96.0	168.0	96.5			33	0	33
Secondary	DUPLEX 1/0	Exisitng	25.05	5.36	0.9540		0.260	96.0	168.0	96.5			33	0	33
Overlashed Bundle	10M	Exisitng	25.00	5.36	0.3060	3.70	0.165	96.0	168.0	96.5	637	20,842	29	0	20,872
											Totals:	20,842	96	0	20,938

Comm	Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Overlashed Bundle 6M	Proposed	21.00	5.64	0.2420	3.70	0.104	96.0	168.0	96.5	436	11,979	5	0	11,985

Fiber **TELE 1.0** Proposed 20.95 5.64 1.0000 0.400 96.0 168.0 96.5 8 0 Totals: 11,979 13 0 11,992

GenericEquip	oment	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Box	Road Sign	Exisitng	7.00	4.62	252.0	0.0	5.00	24.00	1.00		15.00	0	15	16
Box	Road Sign	Exisitng	5.00	4.76	162.0	0.0	5.00	24.00	1.00	~~	15.00	4	139	143
Box	Road Sign	Exisitng	5.00	4.76	342.0	0.0	5.00	24.00	1.00		15.00	-4	139	136
Box	Fiber Demarc	Proposed	17.00	5.12	0.0	0.0	3.00	12.30	3.40		3.00	-2	49	47
Box	Equipment Cabinet	Proposed	13.00	12.70	0.0	0.0	160.00	39.00	18.00		15.00	-318	600	282
Box	Disconnect Switch	Proposed	10.25	6.00	0.0	0.0	17.00	12.60	4.20		8.80	-16	87	71
Box	Elec. Meter	Proposed	8.75	6.50	0.0	0.0	15.00	19.00	5.00		10.00	-15	127	112
Cylinder	Top Shroud	Proposed	31.00	0.06	0.0	0.0	145.00	62.50		16.00		1	1,517	1,518
Cylinder	Galtronics Antenna	Proposed	32.20	0.06	180.0	0.0	19.00	24.70		10.00		0	375	375
Box	Ericsson Antenna	Proposed	29.40	0.06	180.0	0.0	18.00	11.00	5.00		8.00	0	210	210
Box	Ericsson Antenna	Proposed	29.40	0.06	180.0	0.0	18.00	11.00	5.00		8.00	0	210	210
Box	Ericsson Antenna	Proposed	29.40	0.06	180.0	0.0	18.00	11.00	5.00	:	8.00	0	210	210
											Totals:	-349	3,681	3,332

Streetlight		Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Flood Light	Streetlight - 6 ft. Arm	Exisitng	26.00	2.79	252.0	252.0	60.00	24.00	20.00	3.00	72.00	56	1,050	1,107
											Totals:	56	1,050	1,107

Riser		Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
2" U-Guard 60.0° H:28.33	2" U-Guard	Proposed	28.33	4.80	60.0	60.0	28.33	339.96	2.00	2.00	339.96	-4	598	594
											Totals:	-4	598	594

Insulator		Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
J-Hook	J-Hook	Exisitng	25.00	0.00	165.0	165.0	5.00	3.00	0.10	0	0	0
Bolt	Three Bolt	Proposed	21.00	0.00	248.0	158.0	5.00	3.00	0.10	0	0	0
									Totals:	0	1	1

Pole Buckli	ing												
Buckling Constant	Buckling Column Height* (ft)	Buckling Section Height (% Buckling Col. Hgt.)	Buckling Section Diameter (in)	Minimum Buckling Diameter at GL (in)	Diameter at Tip (in)	Diameter at GL (in)	Modulus of Elasticity (psi)	Pole Density (pcf)	Ice Density (pcf)	Pole Tip Height (ft)	Buckling Load Capacity at Height (lbs)	Buckling Load Applied at Height (lbs)	Buckling Load Factor of Safety
2.00	19.64	34.48	8.28	5.48	5.26	9.24	2.13e+6	60.00	57.00	28.33	18,562	186.09	8.06

241/398

Form 1

## APPLICATION AND POLE ATTACHMENT LICENSE

## ANTENNA / NODE LICENSE

	ess PCS, LLC / AT&T - 15213973
Street Address 550 Cochituate Re	
City, State and Zip <u>Framingham</u> , J Date 7/27/2020	MA 01701
Date <u>7/27/2020</u>	
DISTRIBUTED ANTENNA SYSTE	terms and conditions of the CONSTRUCTION REQUIREMENTS FOR  EMS (DAS) ON DISTRIBUTION POLES AGREEMENT, application is hereby  Intenna (Node) Attachment to pole and1
and 1 other attachmen	<u>ntenna (Node)</u> Attachment to pole and <u>1</u> Power Supply nts located in the municipality of <u>Oak Bluffs</u> in the State of
Massachusetts.	To located in the manicipanty of Oak Blairs In the State of
cRAN RCTB OAKB 002. Atta	le Attachment License Application Number 15213973 - ached are my power supply specifications if applicable. The cable's strand eight per foot of cable is 0.12
	Licensee's Name (Print) _Jilian Fancher
NSTAR d/b/a EVERSOURCE	Signature Jilian Fancher
Power Company	Title Site acquisition Specialist
	Tel. No. <u>508-813-1614</u>
	Fax No. <u>617-249-0819</u>
	E-mail jfancher@clinellc.com
Pole Attachment L	nsor use, do not write below this line*********************** icense Application Number 15213973 - cRAN RCTB OAKB 002 is hereby attachment described in this application to attachments to JO1
pole attachment to FO	O <sup>2</sup> pole, attachment to JU <sup>3</sup> pole, Power Supplies and
other attachments located in	the municipality of Oak Bluffs, in the State of Massachusetts as indicated on the
attached Form 3.	
	Licensor's Name (Print)
	Signature Wilall Comeans
(AGREEMENT ID#)	Title Dervisor
	Date 12 14 2020
	Tel. No

## **AUTHORIZATION FOR FIELD SURVEY WORK**

¥	•			
1	37	cer	CE	90.
1	/1	JUL.	DC.	٠.

New Cingular Wireless PCS, LLC

In accordance with Article III & Appendix I of the Pole Attachment Agreement, following is a summary of the charges which will apply to complete a field survey covering Pole Attachment License Application Number 15213973 - cRAN RCTB OAKB 002 in the municipality of Oak Bluffs in the State of Massachusetts.

#### FIELD SURVEY CHARGES

Field Survey	#Poles	Unit Rate	Total
Field Survey Application Fee (includes 1st pole)	1 pole	\$139.00	\$ <u>139.00</u>
Field Survey 2 -200 Poles	0	\$ <u>13.45</u> per Pole	\$
\$ Additional Travel Time*		\$ <u>200.00</u> per Day	\$
TOTAL Charges			<b>\$</b> 139.00

<sup>\*</sup> Based on average of 75 poles surveyed per day, add \$200.00 travel time for each additional day required to complete survey.

Please note, if you calculated the cost incorrectly, your check will be returned and a new check for the correct amount must be received by this office in order to schedule the survey. If you need assistance, please call the **HOTLINE on** 800-340-9822. The required field survey covering Pole Attachment License Application #15213973 - CRAN RCTB OAKB 002 is authorized. I am enclosing an advance payment in the amount of \$139.00.

Licensee's Name (Print) Jilian Fancher	
Agent for New Cingular Wireless PCS	_
Signature Signature Site Acquisition Specialist	
Address 750 W. Center St., Suite 301	
West Bridgewater, MA 02379	
Tel. No. 508-813-1614	
Date: 7/27/2020	

## Billing

Please send monthly electric bills to: AT&T Mobility

c/o Engie Insight – MS7372 P. O. Box 2456 Spokane, WA 99210-2456

Bill email: attlivebills.impact@engie.com

Please include FA #15213973 on the bill.

Please continue to send make ready fees as you currently are.

FORM 3 - EVERSOURCE ITEMIZED Pole Make-Ready Work Charges

PAGE\_1 OF 1

RCE to Complete: Total Poles Surveyed \_\_\_\_\_ Total Poles Requiring NSTAR Make-Ready \_\_\_\_

Appendix IV Form 3 FIELD SURVEY / MAKE READY WORK FORM SURVEYORS: DATE OF SURVEY: CWO #: Verizon MUNIC: Oak Bluffs STATE: MA Exch Code: Munic Code: Licensee New Cingular Wireless PCS LLC LICENSEE NAME: New Cingular LICENSEE APPLICATION #: Wireless PCS LLC 15213973 - cRAN\_RCTB\_OAKB\_002 **EVERSOURCE ELCO NAME: EVERSOURCE** NSTAR APPLICATION # LOCATION POLE # ATT **OWNERSHIP** CHARGE WORK DESCRIPTION TEL RTE / STREET NAME Tel El F/C J.O. YES NO J.U. F.O. TASK #S / \* Height List one pole per line Tel El Tel El Tel El P.S. REMARKS of Att. Riser 64 Circuit Ave., Oak Bluffs, MA 19/ VZ Requesting pole replacement for clearance. Pole 29.5' 41.454517, -70.558951 18 top antenna install with shroud mounted at (replacemen 11'6" and meter at 8' t) TOTALS: Height of Attachment = Height of Licensee Attachment shall be 40" below ELCO MGN unless otherwise noted here by Verizon and EVERSOURCE surveyor. Licensee to complete bold italicized areas only. (Provide ownership information if known)



N E: 1"=20' E: 1"=40'

GRAPHIC SCALE 0 10 20 40 60 FEET

NOTE:

STING UTILITY POLE

1/15 TO BE REPLACED


H NEW CLASS 2 POLE


OTHERS)

- EXISTING

ARM

SUPPORT







may exceed the FCC's the antenna. then 3, for help if you PEDMINDRIA ABOUT

N RD899

BE PLACED OPPOSITE







MODEL	QTY.	L	W	D	WGT.
4402	2	8.0"	8.0"	4.0"	11 LBS

NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.

RRH DETAIL	(2
SCALE: N.T.S	A-2






NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.

## **DIPLEXER DETAIL** (AS REQUIRED)

3 SCALE: N.T.S A-2



2411456

Form 1

# APPLICATION AND POLE ATTACHMENT LICENSE

## ANTENNA / NODE LICENSE

Street Address 550 Cochituate R	less PCS, LLC / AT&T - 15213974
City, State and Zip Framingham,	MA 01701
Date 7/27/2020	
made for a license to make 2 A	e terms and conditions of the CONSTRUCTION REQUIREMENTS FOR EMS (DAS) ON DISTRIBUTION POLES AGREEMENT, application is hereby antenna (Node) Attachment to pole and Power Supply nts located in the municipality of Oak Bluffs in the State of
CRAN RCTB OAKB 003, Atta	ole Attachment License Application Number 15213974 - ached are my power supply specifications if applicable. The cable's strand eight per foot of cable is 0.12.
	Licensee's Name (Print) <u>Jilian Fancher</u>
NSTAR d/b/a EVERSOURCE	Signature Jilian Fancher
Power Company	Title Site acquisition Specialist
	Tel. No508-813-1614
	Fax No. <u>617-249-0819</u>
	E-mail jfancher@clinellc.com
***********************For licer	nsor use, do not write below this line************************************
granted to make 1 Antenna / Node	icense Application Number 15213974 - cRAN RCTB OAKB 003 is hereby attachment described in this application to attachments to JO1
other attachments located in attached Form 3.	O <sup>2</sup> pole, attachment to JU <sup>3</sup> pole, Power Supplies and the municipality of Oak Bluffs, in the State of Massachusetts as indicated on the
	Licensor's Name (Print) RICMAR CMEAU
	Signature Relabel Compare
(AGREEMENT ID#)	Title SuperVISUr
	Date 12/3/2020
	Tel. No.

# **AUTHORIZATION FOR FIELD SURVEY WORK**

Licensee:

New Cingular Wireless PCS, LLC

In accordance with Article III & Appendix I of the Pole Attachment Agreement, following is a summary of the charges which will apply to complete a field survey covering Pole Attachment License Application Number 15213974 - cRAN RCTB OAKB 003 in the municipality of Oak Bluffs in the State of Massachusetts.

### FIELD SURVEY CHARGES

Field Survey	#Poles	Unit Rate	Total
Field Survey Application Fee (includes 1st pole)	1 pole	\$139.00	\$ <u>139.00</u>
Field Survey 2 -200 Poles	0	\$_13.45per Pole	\$
\$ Additional Travel Time*	/ <u> </u>	\$200.00 per Day	\$
TOTAL Charges			<b>\$</b> 139.00

<sup>\*</sup> Based on average of 75 poles surveyed per day, add \$200.00 travel time for each additional day required to complete survey.

Please note, if you calculated the cost incorrectly, your check will be returned and a new check for the correct amount must be received by this office in order to schedule the survey. If you need assistance, please call the **HOTLINE on** 800-340-9822. The required field survey covering Pole Attachment License Application #15213974 - cRAN RCTB OAKB 003 is authorized. I am enclosing an advance payment in the amount of \$139.00.

Licensee's Name (Print) Jilian Fancher
Agent for New Cingular Wireless PCS
Signature Jilian Fancher
Title Site Acquisition Specialist
Address 750 W. Center St., Suite 301
West Bridgewater, MA 02379
Tel. No. 508-813-1614
Date: <u>7/27/2020</u>
West Bridgewater, MA 02379 Tel. No. 508-813-1614

## **Billing**

Please send monthly electric bills to: AT&T Mobility

c/o Engie Insight – MS7372 P. O. Box 2456 Spokane, WA 99210-2456

Bill email: attlivebills.impact@engie.com

Please include FA #15213974 on the bill.


Please continue to send make ready fees as you currently are.


PAGE\_1\_ OF\_1\_

FORM 3 -- EVERSOURCE ITEMIZED Pole Make-Ready Work Charges PAGE
RCE to Complete: Total Poles Surveyed \_\_\_\_\_\_ Total Poles Requiring NSTAR Make-Ready \_\_\_\_\_

	SURVEYORS:				DAT	EO	FSID	PVET	7.		DY WC							
Verizon					DATE OF SURVEY: MUNIC: Oak Bluffs STATE:			170 - N.F.A		CWO #:								
Licensee	New Cingular Wi	ireless	s PCS	S LLC	LICE	LICENSEE NAM			CENSEE NAME: New Cingular					Exch Code: Munic Code:  LICENSEE APPLICATION #:				
EVERSOURCE	RSOURCE											15213974 - CRAN RCTB OAKB 003						
LOCA	ATION	POI	E#	ATT		OWNERSHIP CHARGE					CHAI	DCE	NSTAR APPLICATION #					
TEL RTE / STRI		Tel	El		_	J.O. J.U.		F.(	2	YES NO		WORK DESCRIPTION						
	ole per line			P.S. Riser	Tel			Tel El	Tel E		IEG	NO	TASK #S / REMARKS	* Height of Att.				
11 Massasoit Ave., Oak Bluffs, MA 41.453177, -70.557071		fs, MA			VZ	V	Pole top antenna install with shroud m at 11'6" and meter at 8'	Pole top antenna install with shroud mounted at 11'6" and meter at 8'	27' pole top									
														*				
														*				
												-						
										-								
														*				
														*				
	TOTALS:				i								oted here by Verizon and EVERSOURCE surveyor.					










NOTE:










MODEL	QTY.	L	W	D	WGT.			
4402	2	8.0"	8.0"	4.0"	11 LBS			

NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.


RRH DETAIL	(2)
SCALE: N.T.S	A-2



NO BATTERY BACKUP OR AUXILIARY OUTLETS


FOR BACKUP POWER ARE BEING PROVIDED

IN THIS DESIGN



NOTE: MOUNT PER MANUFACTURER'S SPECIFICATIONS.





STONEHOUSE SIGNS INC. P/N RD899

Form 1

## APPLICATION AND POLE ATTACHMENT LICENSE

## ANTENNA / NODE LICENSE

	ess PCS, LLC / AT&T - 15213958
Street Address 550 Cochituate Rd	
City, State and Zip Framingham. N	MA 01701
Date 7/27/2020	
In accordance with the	terms and conditions of the CONSTRUCTION REQUIREMENTS FOR
	MS (DAS) ON DISTRIBUTION POLES AGREEMENT, application is hereby
	ntenna (Node) Attachment to pole and1 Power Supply
	nts located in the municipality of Oak Bluffs in the State of
Massachusetts.	
cRAN RCTB OAKB 004. Atta	le Attachment License Application Number <u>15213958 -</u> ched are my power supply specifications if applicable. The cable's strand eight per foot of cable is <u>0.12</u>
	Licensee's Name (Print) <u>Jilian Fancher</u>
NSTAR d/b/a EVERSOURCE	SignatureQilian Fancher
Power Company	Title Site acquisition Specialist
	Tel. No508-813-1614
	Fax No. 617-249-0819
	E-mail jfancher@clinellc.com
Pole Attachment I granted to make 1 Antenna/Node pole attachment to Fo	nsor use, do not write below this line************  License Application Number 15213958 - cRAN RCTB OAKB 004 is hereby attachment described in this application tolattachments to JO¹  D² pole,attachment to JU³ pole,Power Supplies and the municipality of Oak Bluffs, in the State of Massachusetts as indicated on the
	Licensor's Name (Print) Richard Compeu
	Signature Uccland Comesci
(AGREEMENT ID#)	Title Supervisor
	Date 10 2020
	Tel. No.

# **AUTHORIZATION FOR FIELD SURVEY WORK**

Licensee:

New Cingular Wireless PCS, LLC

In accordance with Article III & Appendix I of the Pole Attachment Agreement, following is a summary of the charges which will apply to complete a field survey covering Pole Attachment License Application Number 15213958 - cRAN RCTB OAKB 004 in the municipality of Oak Bluffs in the State of Massachusetts.

## FIELD SURVEY CHARGES

Field Survey	#Poles	<u>Unit Rate</u>	Total
Field Survey Application Fee (includes 1st pole)	1 pole	\$139.00	\$ <u>139.00</u>
Field Survey 2 -200 Poles	0	\$ <u>13.45</u> per Pole	\$
\$ Additional Travel Time*	(	\$ <u>200.00 p</u> er Day	\$
TOTAL Charges			\$ <u>139.00</u>

<sup>\*</sup> Based on average of 75 poles surveyed per day, add \$200.00 travel time for each additional day required to complete survey.

Please note, if you calculated the cost incorrectly, your check will be returned and a new check for the correct amount must be received by this office in order to schedule the survey. If you need assistance, please call the **HOTLINE** on 800-340-9822. The required field survey covering Pole Attachment License Application #15213958 - cRAN RCTB OAKB 004 is authorized. I am enclosing an advance payment in the amount of \$139.00.

Licensee's Name (Print) Jilian Fancher
Agent for New Cingular Wireless PCS
Signature Oilian Fanchar Title Site Acquisition Specialist
Address 750 W. Center St., Suite 301 West Bridgewater, MA 02379
Tel. No. 508-813-1614
Date: 7/27/2020

### Billing

Please send monthly electric bills to: AT&T Mobility c/o Engie Insight – MS7372 P. O. Box 2456

Spokane, WA 99210-2456

Bill email: attlivebills.impact@engie.com


Please include FA #15213958 on the bill.


Please continue to send make ready fees as you currently are.

FORM 3 - EVERSOURCE ITEMIZED Pole Make-Ready Work Charges


PAGE\_\_1\_ OF 1

RCE to Complete: Total Poles Surveyed \_\_\_\_\_ Total Poles Requiring NSTAR Make-Ready \_\_\_\_ Appendix IV Form 3 FIELD SURVEY / MAKE READY WORK FORM SURVEYORS: DATE OF SURVEY: CWO #: Verizon MUNIC: Oak Bluffs STATE: MA Exch Code: Munic Code: Licensee New Cingular Wireless PCS LLC LICENSEE NAME: New Cingular LICENSEE APPLICATION #: Wireless PCS LLC 15213958 - cRAN RCTB OAKB 004 EVERSOURCE ELCO NAME: EVERSOURCE **NSTAR APPLICATION #** LOCATION POLE # ATT OWNERSHIP CHARGE WORK DESCRIPTION TEL RTE / STREET NAME Tel El F/C J.O. J.U. F.O. YES NO TASK #S / \* Height List one pole per line Tel El Tel El Tel El P.S. REMARKS of Att. Riser 2 Pennecook Ave, Oak Bluffs, MA 63/ VZ Pole top antenna install with shroud mounted 28'4" pole 41.452216, -70.553572 at 11'6" and meter at 8' TOTALS: Height of Attachment = Height of Licensee Attachment shall be 40" below ELCO MGN unless otherwise noted here by Verizon and EVERSOURCE surveyor. Licensee to complete bold italicized areas only. (Provide ownership information if known)







AT&T locations (green dots) and proposed locations (blue dots) in and around Oak Bluffs, MA




# Current AT&T Coverage in Oak Bluffs, MA




AT&T locations (green dots) and proposed locations (blue dots) near Town Beach





# Current AT&T Coverage near Town Beach, Oak Bluffs




# Proposed AT&T Coverage near Town Beach, Oak Bluffs









## DONALD L. HAES, JR., CHP, CLSO

PO Box 198, Hampstead, NH 03841

Radiation Safety Specialist 603-303-9959

Email: donald haes chp@comcast.net

July 1, 2019

I have reviewed the information pertinent to the hypothetical installation of an AT&T Personal Wireless Services (PWS) omni-directional panel antenna installation on a utility pole. I have analyzed the scenario where there would be one antenna mounted with a centerline height of 30' above ground level (AGL). This analysis considers the contributions of the AT&T PWS transmitters operating at the following supplied parameters:

PWS Service	Frequency (MHz)	Transmitter Output Power	Antenna Manufacturer / Model Number	Antenna Gain (dBd)	
PCS LTE	1930-1950	40 watts		7.33	
5G: U-NII-1	5150-5250	1	EXTENT™ P6480i (See Appendix A)	7.50	
5G: U-NII-3	5725-5850	1 watt (maximum)	-	7.53	

The calculated values of RF fields are presented as a percent of current Maximum Permissible Exposures (%MPE) as adopted by the Federal Communications Commission (FCC). Theoretical RF field calculations for the near proximity of RF source terms (in this case the AT&T transmit antennas), however, are not straight forward. For these theoretical calculations, a cylindrical model was used, where "spatially averaged plane-wave equivalent power densities parallel to the antenna may be estimated by dividing the net antenna input power by the surface area of an imaginary cylinder surrounding the length of the radiating antenna". Calculations using "far-field" formula would considerably overestimate the resultant power densities. The calculations performed for this analysis still accurately represent the "worst case" and assume 100% usage of all the antennas.

The power density estimates can be calculated by using the formula:

$$S = \underbrace{P_{net}}_{\mathbf{2} \bullet \Pi \bullet \mathbf{R} \bullet \mathbf{h}}$$
 Where:  $P_{net} = \text{Net power to antenna (watts)}$  
$$R = \text{Distance (range) from antenna}$$

h = aperture height of the antenna

The results of the RF field calculations for a single antenna are depicted in Figure 1 showing a side view representation demonstrating the directionality of the RF energy propagating from the antenna.

Note: The analyses, conclusions and professional opinions are based upon the precise parameters and conditions of this typical AT&T "small cell" installation on a utility pole with a mounting centerline height of 30' AGL. Utilization of these analyses, conclusions and professional opinions for any personal wireless services installation, existing or proposed, other than the aforementioned has not been sanctioned by the author, and therefore should not be accepted as evidence of regulatory compliance.




Figure 1: Results of RF field calculations for a typical AT&T antenna installation on a utility pole at 30' (AGL) showing profile view

#### **CONCLUSION**

Theoretical RF field calculations data indicate the summation of the AT&T RF contributions on a typical utility pole would be well within the established RF exposure guidelines; see Figure 1. Although the calculations assume a typically low mounting height of 30' AGL, some applications may require the antenna to be mounted higher. In these circumstances, the increased separation between the ground and antenna would result in an even lower general public exposure levels. These results indicate there could be more similar installations at these locations, and still be within Federal and State guidelines for RF exposure. This report provides written proof that the proposed facilities would comply with the FCC RF exposure guidelines. These small cell antenna installations proposed by AT&T would not produce significant changes to the ambient RF environment.

## DONALD L. HAES, JR., CHP, CLSO

Radiation Safety Specialist 603-303-9959

PO Box 198, Hampstead, NH 03841

Email: donald\_haes\_chp@comcast.net

#### STATEMENT OF CERTIFICATION

- 1. I certify to the best of my knowledge and belief, the statements of fact contained in this report are true and correct.
- 2. The reported analyses, opinions, and conclusions are limited only by the reported assumptions and limiting conditions, and are personal, unbiased professional analyses, opinions and conclusions.
- 3. I have no present or prospective interest in the property that is the subject of this report and I have no personal interest or bias with respect to the parties involved.
- 4. My compensation is not contingent upon the reporting of a predetermined energy level or direction in energy level that favors the cause of the client, the amount of energy level estimate, the attainment of a stipulated result, or the occurrence of a subsequent event.
- 5. This assignment was not based on a requested minimum environmental energy level or specific power density.
- 6. My compensation is not contingent on an action or event resulting from the analyses, opinions, or conclusions in, or the use of, this report.
- 7. The consultant has accepted this assessment assignment having the knowledge and experience necessary to complete the assignment competently.
- 8. My analyses, opinions, and conclusions were developed and this report has been prepared, in conformity with the *American Board of Health Physics* (ABHP) statements of standards of professional responsibility for Certified Health Physicists.

Date: July 1, 2019

Donald L. Haes, Jr.

Certified Health Physicist

#### APPENDIX A



10" x 24" Outdoor Pseudo Omni Canister Antenna [1695-2400, 3550-3700 and 5150-5950 MHz]

## EXTENT™ P6480i

#### **Description:**

- Pseudo Omni Canister Antenna for Outdoor DAS and Small Cells.
- 4x ports for AWS/PCS/WCS Band 1695-2400 MHz
- 4x ports for CBRS Band 3550-3700 MHz
- 2x ports for 5GHz Band 5150-5950 MHz



1695-2400, 3550-3700 and 5150-5950 MHz Pseudo Omni Canister Antenna

Frequency Band [MHz]	1695-2180	2180-2400	3550-3700	5150-5950			
Input Connector Type	4x 4.3-	10 DIN(F)	4x 4.3-10 DIN(F)	2x 4.3-10 DIN(F)			
Isolation (typ.)	-2	0 dB	-25 dB	-25 dB			
Inter-band Isolation	-30 c	dB (typ)	-30 dB (typ)				
VSWR/Return Loss		1.5:1(Typ.) 1.7:1(Max	c) / 14.0 dB(Typ.) 11.8dB(Max.)				
Impedance	50 Ω						
Polarization	Dual slant 45° (±45°)						
Horizontal Beamwidth		Dual slant 45° (±45°)           Omni (360°)         15°         12°         15°           9 dBi         9.5 dBi         8.5 dBi	)mni (360°)				
Vertical Beamwidth	15°	12°	15°	19*			
Max. Gain	9 dBi	9.5 dBi	8.5 dBi	6 dBi(Max.)			
Avg. Gain	7.5 dBi	8 dBi	8 dBi	3 dBi			
Downtilt			0*				
Max Power / Port	150	Watts	100 Watts	10 Watts			
PIM @ 2x43 d8m	«-1 <u>\$</u>	i3 dBc	N/A	N/A			

Operating Temperature	-40° to 158°F (-40° to +70°C)
Antenna Weight	19 lbs (9 kg)
Antenna Diameter	10" (254 mm)
Antenna Height	24.7" (628 mm)
Radome Material	ASA
RoHS	Compliant
Radome Color	Gray, Brown, 3M <sup>™</sup> Conceal Film, Custom Colors Possible
Ingress Protection	Outdoor (IP65)
Wind Survival Rating	150 mph (241 km/h)
Shipping Dimensions - L x W x D	30°x19°x19° (762x483x483 mm)
Shipping Weight (Gross Weight)	26 lbs (12 kg)

Nekrase Date: March 02, 2017; Revision; S.1.: REDIFGABB

Copyright © 2017 - Galtronics Corporation Ltd.
Proprietary Information, All rights reserved. Galtronics reserves the right to modify or amend any entenna or specification withhout prior notice.

WWW.GALTRONICS.COM

CVEC - Oak Bluffs_01.22.21	\$ 79.17	BS211	01199-5211	3.85% of total CVEC NMC cash-out from Nexamp
CVEC - OBHA1913-90027963	\$ 7.48	BS211	01199-5211	2.56% of total NMC cash-out for Harwich Landfill PV
County of Dukes County	\$ 6,006.50	BS845	01122-4845	Parking revenue February FY21
Paul Hartel	\$ 725.00	29PKNG	29176-4800	Parking Mitigation/ 35 Circuit
Reynolds, Rappaport, Kaplan &				
Hackney	\$ 2,025.00	29PAR	29631-4800	Ocean Park / Catalpa tree/ Parks department

		Business/Common Vic BS436		Building/	B1334	Fire/FD335		int ic/BS419	Delinery.	i/Livery S434	Aut	to BS370
Dockside Inn	\$ 145.00	\$ 50	.00	\$	50.00	\$ 45.0	00					
Lazy Frog	\$ 145.00	\$ 50	.00	\$	50.00	\$ 45.0	00					
Nautilus Trading	\$ 145.00	\$ 50	.00	\$	50.00	\$ 45.0	00					
Oak Bluffs Land and Wharf Co	\$ 145.00								\$	145.00		
Oak Bluffs Land and Wharf Co	\$ 255.00								\$	255.00		
Sun n Fun	\$ 395.00			\$	50.00	\$ 45.0	00				\$	300.00
titticut Follies	\$ 145.00	\$ 50	.00	\$	50.00	\$ 45.0	00					
Chickering	\$ 40.00	Shellfish recreational										
Davis	\$ 40.00	Shellfish recreational										
Oslyn	\$ 40.00	Shellfish recreational										
Sittard	\$ 5.00	Shellfish recreational										